


Landsat 7 Processing System (LPS) Software Configuration Guide

Revision 1

March 1998



National Aeronautics and
Space Administration

Goddard Space Flight Center
Greenbelt, Maryland

Landsat 7 Processing System (LPS) Software Configuration Guide

March 1998

Prepared by:

| | |
|---|------|
| Charlene Binley Software Configuration Manager | Date |
|---|------|

Quality Assured by:

| | |
|---|------|
| Sheila Whisonant Quality Assurance Officer | Date |
|---|------|

Concurred by:

| | |
|--|------|
| Khemraj Sharma Integration and Test Department Deputy Manager | Date |
|--|------|

Approved by:

| | |
|------------------------------------|------|
| Nate Daniel LPS Element Manager | Date |
|------------------------------------|------|

| | |
|------------------------------------|------|
| Joy Henegar LPS Project Manager | Date |
|------------------------------------|------|

Goddard Space Flight Center
Greenbelt, Maryland

Preface

This document is a software configuration guide for the Landsat 7 Processing System (LPS) developed at Computer Sciences Corporation (CSC). The Software Configuration Management task assigned to LPS is responsible for updating this document until the system is turned over to the EROS Data Center in Sioux Falls, South Dakota.

Revision 1 of this LPS Software Configuration Guide (document number 514-3SCG/0197) contains changes reflecting Release 3.0.

Comments, questions, or proposed changes to this document should be addressed to

Landsat 7 Technical Area Manager
Goddard Space Flight Center
Greenbelt, Maryland 20771

Abstract

This document describes the allocation of software and data to physical disks on the development and operational Landsat 7 Processing System (LPS). Furthermore, it describes the software configuration management being applied to LPS, which includes procedural information for installing LPS and for building the LPS executables and installing them for testing and operations.

Change Status Log

| Document No.: 514-3SCG/0197 Title: <i>Landsat 7 Processing System (LPS) Software Configuration Guide</i> | | | |
|---|-------------|----------------|---------------------------|
| Change | Date | Affected Pages | Remarks |
| | July 1996 | | Review |
| | August 1997 | | Signature |
| Revision 1 | March 1997 | All | Based on CCR LPS970222 |
| | | | |

Contents

1. Introduction

| | | |
|-------|--|-----|
| 1.1 | Purpose..... | 1-1 |
| 1.2 | Environments..... | 1-1 |
| 1.3 | Directory Structure for the Operational Environment..... | 1-1 |
| 1.4 | Directory Structure for the Test Environment..... | 1-1 |
| 1.5 | Directory Structure for the Development Environment..... | 1-1 |
| 1.5.1 | Directory for Structure and Executables on the Development String..... | 1-3 |

2. Physical and Logical Disk Assignments

| | | |
|-------|---|-----|
| 2.1 | Operational String Disks..... | 2-1 |
| 2.1.1 | Logical-to-Physical Disk Mapping of Operational String..... | 2-1 |
| 2.2 | Backup String Disks (String 5)..... | 2-2 |
| 2.2.1 | Logical-to-Physical Disk Mapping of Backup String..... | 2-2 |

3. Configuration Management

| | | |
|-------|--|------|
| 3.1 | CM Directory Structure in the Development String..... | 3-1 |
| 3.2 | Building the System in the Development String..... | 3-2 |
| 3.2.1 | Preparation for a Build..... | 3-2 |
| 3.2.2 | Detailed Build Process Using the Command Line Version..... | 3-7 |
| 3.2.3 | Building for Operations..... | 3-12 |
| 3.3 | Populating the Runtime Directories..... | 3-12 |
| 3.3.1 | Development System..... | 3-12 |
| 3.3.2 | Operational System..... | 3-12 |

| | | |
|-------|---|------|
| 3.4 | LPS Release Types..... | 3-15 |
| 3.4.1 | Build Notes from a Mini_Release or Patch..... | 3-16 |
| 3.4.2 | Build Notes for an Engineering Mode..... | 3-16 |

Appendix A. Checklist for LPS Software Installation

Appendix B. Sample Configuration Management's .cshrc File

Appendix C. Configuration Management Scripts

Appendix D. Sample Environment Variables for System Test

Appendix E. Sample Tester's .cshrc File

Appendix F. Installing the IRIX Operating System

Appendix G. Installing Network Time Protocol

Appendix H. Installing ORACLE

Appendix I. Sample Environment Variables for CM

References

Acronyms

List of Tables

| | | |
|-----|--|-----|
| 2-1 | Summary of Disk Allocation for Operational String..... | 2-1 |
| 2-2 | Summary of Disk Allocation for Backup String..... | 2-2 |
| 3-1 | Explanation of Terms in Figure 3-2..... | 3-5 |

List of Figures

| | | |
|-----|--|-----|
| 1-1 | Operational Environment Directory Structure..... | 1-2 |
| 1-2 | String 5 – Test Environment Directory Structure..... | 1-2 |
| 1-3 | Basic Structure for Storing Developed Software..... | 1-3 |

| | | |
|-----|---|------|
| 2-1 | Operational Hardware Configuration..... | 2-3 |
| 3-1 | CM Directory Structure in the Development String..... | 3-1 |
| 3-2 | Development Directory Structure..... | 3-4 |
| 3-3 | Development Test Directory Structure..... | 3-10 |
| 3-4 | Operations Directory Structure..... | 3-13 |
| 3-5 | Development Runtime Directory Structure..... | 3-14 |
| 3-6 | Operational Runtime Directory Structure..... | 3-14 |

Section 1. Introduction

1.1 Purpose

This Landsat 7 Processing System (LPS) Software Configuration Guide is intended to provide in-depth procedural information for applying configuration management (CM) to the LPS application software located at the customer site. It also explains how to build the LPS executables and where the new executables can be tested for verification.

Applicable documentation for this guide is listed in the References section.

1.2 Environments

LPS consists of five individual computers with identical operational environments. Each computer and its operational environment defines a string. Four of the strings support normal operations at all times. The fifth string is available for LPS test and maintenance support, as required, and as a backup string to the four operational strings. References 1 through 3 provide more specific information on the five LPS strings.

LPS provides a development environment on the fifth string for maintenance programmers who perform software enhancements and software corrections.

LPS also provides a test environment on the fifth string to test and verify changes to the LPS software before they are propagated to the four operational strings. The purpose and function of the test environment is further described in Reference 1.

LPS provides a CM environment on the fifth string to control access to the latest LPS operational software. LPS uses the Polytron Version Control System (PVCS) Version Manager as its CM tool.

1.3 Directory Structure for the Operational Environment


The directory structure of the operational environment (Figure 1–1) is defined in Reference 1. The four operational strings contain executable code and do not contain any application source files. New versions of the executables are generated and tested on the backup string and, if approved, promoted to the operational environment on the four LPS strings, as well as the operational directory on the fifth string.

1.4 Directory Structure for the Test Environment

The directory structure of the test environment is reflected in Figure 1–2.

1.5 Directory Structure for the Development Environment


The directory structure of the development environment on string 5 stores developed software as shown in Figure 1–2. Source code (Rs) is stored in src and include subdirectories; the executables (Rx) for the LPS applications are stored in the bin directory.



¹Installation of the operating system, IRIX 6.2, automatically populates the miscellaneous CO1

²Current version of the executables; see Figure 3–4 for the operational string structure.

Figure 1–1. Operational Environment Directory Structure




* See Figure 3–3 for more detail.
 ** See Figure 3–4 for more detail.

Figure 1–2. String 5 – Test Environment Directory Structure

1.5.1 Directory Structure for Source and Executables on Development String

The basic structure for storing developed software on string 5 is shown in Figure 1–3. Figures 3–2 and 3–3 show more detail of the directory structure. The “pvcs” subdirectory stores source code, and the “cm” subdirectory stores a copy of the source and executables of the current and previous releases, as well as CM-related scripts. Separate subdirectories for each release under “cm” permit quick access to the current and previous source code. The “ops” subdirectory houses the most current LPS executables. Once accepted, the LPS executables are populated to the appropriate subdirectory on strings 1 to 4. Thus, the executables will be stored on all five strings.



Ro = source for all LPS releases to date
 Rs = current release's source for that environment
 Rs-1 = previous release's source for that environment
 Rx = current release's executables for that environment
 Rx-1 = previous release's executables for that environment

¹See Figure 3-1

²See Figure 3-2

³See Figure 3-3

Figure 1-3. Basic Structure for Storing Developed Software

Section 2. Physical and Logical Disk Assignments

Section 2 describes the physical disks on the operational and backup string disks and their logical allocation for the development, test, and operational environments. Appendix A provides a checklist for installing the required LPS-related software.

2.1 Operational String Disks

Each operational string has a system disk and two redundant arrays of inexpensive devices (RAIDs), one for incoming data from the Landsat Ground Station (LGS), and a second RAID for temporary storage of LPS output data sets awaiting retrieval by the Earth Observing System (EOS) Core System.

2.1.1 Logical-to-Physical Disk Mapping of Operational String

This section describes the logical disk allocation defined for the physical disks. Table 2–1 summarizes the allocation of the logical file systems to physical disks. This allocation is expected to meet operational needs.

Table 2–1. Summary of Disk Allocation for Operational String

| Disk | File System | Use | Allocation |
|--------|--------------|------------|---|
| System | / | Operations | IRIX 6.2 |
| | /usr | | ORACLE (Server and ORACLE Developer 2000 1.3.1) |
| | /usr/LPS/ops | | Other commercial off-the-shelf (COTS) software (Section 2.1.1.1) LPS executables |
| RAID 1 | /u01 | Front end | Raw wideband data |
| RAID 2 | /u02 | Back end | LOR output files |

2.1.1.1 System Disk in Each Operational String

At any one time, the system disk on each operational string will contain the following:

- Operating system and associated files
- One operational instance of the LPS database, one for each environment (development, test, and operational)
- COTS
 - IRIX 6.2 (operating system)
 - NROFF (part of Documenters Workbench in IRIX 6.2)
 - ONC3/NFS 6.2
 - IRIS Development Option 6.2 (CaseVision Workshop 2.6)

- IRIX 6.2 Applications
- IRIS Power C 6.2
- ORACLE Server 7.3.2
- ORACLE Development 2000 1.3.1
- Network Time Protocol, Version 2.0 (SGI freeware)

The version numbers may change with each software turnover and will be noted in the turnover package.

2.1.1.2 Redundant Array of Inexpensive Devices

2.1.1.2.1 Input RAID

The input RAID on each operational string contains data received from the LGS that is ingested by the raw data capture subsystem (RDCS). The amount and frequency of this data are discussed in Reference 1.

2.1.1.2.2 Output RAID

The output RAID on each operational string contains actual LPS output files. Users may request these files by notifying LPS. Output files are available to users via transfer protocol software.

2.2 Backup String Disks (String 5)

The backup string (string 5) has a system disk, an LPS development (or application) disk, and two RAIDs. The first RAID is reserved for storage of incoming data from LGS. As a development string, the second RAID is reserved for temporary storage of test data sets. As a backup to an operational string, the second RAID is reserved for temporary storage of LPS output data sets awaiting retrieval by the EOS Core System. Figure 2–1 shows the relationship of the backup string to the operational strings (strings 1 to 4).

2.2.1 Logical-to-Physical Disk Mapping of Backup String

This section describes the logical disk allocation defined for the physical disks. Table 2–2 summarizes the allocation of the logical file systems to physical disks.

Table 2–2. Summary of Disk Allocation for Backup String

| Disk | File System | Use | Software Allocation |
|-----------------|--------------------|-------------|---|
| System | /usr | Operations | Same as operational strings |
| LPS Application | /usr | Development | LPS software |
| RAID 1 | /u01 | Front end | Development: Test data only As operational backup: |

| Disk | File System | Use | Software Allocation |
|--------|-------------|----------|--|
| | | | Raw wideband data |
| RAID 2 | /u02 | Back end | Development: Test data sets only As operational backup: Level zero R output files |

2.2.1.1 System Disk (String 5)

At any one time, the system disk on string 5 will contain the following:

- Operating system and associated files
- Three distinct instances of the LPS database, one for each environment (development, test, and operational)
- PVCS library
- Development environment directories (see Section 1.3)
- Government off-the-shelf (GOTS): frame_sync libraries
- COTS
 - Hierarchical data format (HDF) libraries
 - IRIX 6.2 (operating system)
 - NROFF (part of Documenters Workbench in IRIX 6.2)
 - NC3/NFS 6.2
 - IRIS Development Option 6.2 (CaseVision Workshop 2.6)
 - IRIX 6.2 Applications
 - IRIS Power C 6.2
 - ORACLE Server 7.3.2
 - ORACLE Development 2000 1.3.1
 - Network Time Protocol, Version 2.0 (SGI freeware)

2.2.1.2 Redundant Array of Inexpensive Devices (String 5)

2.2.1.2.1 Input RAID

At any one time, the input RAID contains raw data files used for testing

- Image Assessment System (IAS) parameters from the calibration parameter file
- Executables that have been modified to provide enhancements to LPS software or to correct errors

2.2.1.2.2 Output RAID

At any one time, the output RAID contains

- Test environment output data files resulting from IAS parameter, other LOR parameters or threshold tests
- Development environment output data files resulting from tests of enhanced or modified software

Section 3. Configuration Management

Section 3 contains the CM directory structure and build process for LPS in the development string at Computer Sciences Corporation (CSC). All software written to support the operational LPS will be maintained and controlled by the configuration manager using the CM tool, PVCS Version Manager, which resides on the development string only. All builds must occur in a CM work directory that is outside of PVCS.

3.1 CM Directory Structure in the Development String

All LPS software builds must occur in the CM work directory called *lpswork*. All source and control files under configuration control are stored in the */pvcs/LPS/archives* directory. Controlled files include script files and data files needed by certain subsystems. The CM directory structure is illustrated in Figure 3–1. See Appendix B for a sample of the *.cshrc* file for CM.




Figure 3–1. CM Directory Structure in the Development String

3.2 Building the System in the Development String

The software written to support LPS is developed, turned over to CM, stored in PVCS, extracted into the CM work directory, and then built for testing. The executables are delivered to lps005 at the Earth Resources Observation System (EROS) Data Center (EDC) for acceptance testing via the file transfer process. They are then copied to operational directories only on approval of acceptance test and operation management.

The process for building a version of LPS is always performed on the development string.

Scripts to build the LPS structure and manage PVCS activities exist and are listed in Section 3.2.1.3.

3.2.1 Preparation for a Build

Preparation for a build involves

- Backup pvcs and current cm directories
- Reviewing the turnover package
- Checking that all COTS and GOTS software are the correct versions and are installed, including the required instances of the database in the test environment
- Adding the new version label to the current version in PVCS before checking in delivered units
- Making necessary script changes to reflect LPS structural change in the CM work directory and PVCS
- Checking the .cshrc and the .lpsdevrc files for correct environment setups; the .lpsrc is installed with the executables at the test site
- Checking new and modified units into PVCS (Note: Keep a copy of the delivered software because the files are physically moved into PVCS.)

3.2.1.1 Turnover Package

The turnover package contains all build information (a list of new, modified, and deleted units), environment changes, and build instructions.

3.2.1.2 Required COTS and GOTS to Build

Section 2 identifies the COTS and GOTS software required for a build. The correct versions of the COTS and GOTS software should be noted in each build's turnover package. Some of them include the following:

- IRIX 6.2

- NROFF (part of Documenters Workbench in IRIX 6.2)
- ORACLE 7.3.2
- HDF4.1r
- HDF-EOS2.1v1.00
- Frame_Sync libraries

The `usr/cm/LPS` subdirectory should contain an `hdf` directory with appropriate versions of the HDF libraries so that a link can be made to it from the `COTS` subdirectory in the `usr/cm/lpswork/COTS` directory.

3.2.1.3 Script Changes

All of the following scripts (except `LPS_makedir`) are located in `$HOME/cm/scripts`. `LPS_makedir` is the only PVCS-controlled script at this time (`/usr/pvcs/LPS/archives/LPS_makedir,v`), which is extracted from PVCS to the `$HOME/cm/LPS` directory. Appendix C contains a hardcopy of these scripts. They may require changes if the LPS structure changes.

- `new_check`: checks units (whole system) into PVCS
- `new_get` checks units out of PVCS into the work directory
- `LPS_makedir` recreates the LPS working directory structure called “*lpswork*” where the build will take place. It also extracts the most current `lmake` and `install` scripts and places them in the appropriate subdirectories. The work directory is shown in Figure 3–2. (Table 3–1 provides an explanation of the terms used in Figure 3–2.)
- `setup_st_deliv` creates the necessary subdirectory structure that will be populated to the test site. It should be updated as required; i.e., build number and other changes.

These scripts change when the LPS structure changes. All scripts should reflect the desired version label.

A copy of these scripts may need to be modified for patches or partial builds.

Any structural modifications to PVCS are made manually.

3.2.1.4 Changes to the `LPS_makedir` Script

The `LPS_makedir` script builds the complete LPS tree structure in the CM work directory, *lpswork*, prior to checking units out of PVCS for a build. It is a controlled script and requires editing the version label within the script whenever a new build takes place. LPS structural changes should also be made when necessary. Test the script before returning it to PVCS; this will require either checking in one copy of the modified `lmake` and `install` scripts into `/usr/pvcs/LPS/archives` with the correct version label or adding the correct version label to the current unchanged scripts stored in PVCS.

1. Extract the LPS_makedir script from PVCS:

```
cd /usr/cm/LPS
```

```
get -l $PVCS_LPS/archives/LPS_makedir,v
```

Table 3–1. Explanation of Terms in Figure 3–2

| Term | Explanation |
|-----------------|---|
| .env | Environment file that holds environment variables for the system and/or subsystem |
| bin | Holds executables |
| data | Holds data files; these directories may be subdivided further, perhaps for different contact periods |
| db | Holds global database routines and include files |
| db_script | Holds the instruction file and scripts to recreate the current database |
| global | Holds global routines and global include files; the global directory under the subsystem_name directory contains units common to the different subsystem processes, but not to the project as a whole |
| include | Holds include files |
| man | Holds the man pages for LPS |
| obj | Holds object files and db and global libraries |
| scripts | Holds make files and any other scripts |
| src | Holds source files |
| src# (# = 1–13) | Holds source files that create an executable |
| subsystem_name | Provides the top-level directory for each subsystem: IDPS, LTDS, MACS, MFPS, PCDS, RDCS, and RDPS |
| tools | Holds useful tools for developers and maintainers, such as alignments of code program and cadre tools |
| ui | Holds user interface files |

2. Edit the script and change the version label (e.g., B3.1 or R1.0) or group label (e.g., ST) for the lmake and install files desired and make the necessary structural changes; B = build and R = release.
3. Save the changed file.
 - a. If the directory structure changes, test the script:
 - Backup the current lpswork directory or remove it.

cd \$HOME

To backup: **mv /usr/cm/lpswork bak.lpswork**

To remove: **rm -rf /usr/cm/lpswork**

- If the lmake or install scripts remain unchanged, add the version label to these two units in PVCS if not already done (see Section 3.2.1.6):

vcs -vR3.0:R2.1 /usr/pvcs/LPS/archives/install,v

(replace “install” with “lmake” and repeat the command)

- If the lmake or install scripts are modified, check the lmake and install scripts into PVCS:

put -vB# or R# /usr/cmlpswork/install /usr/pvcs/LPS/archives/install,v

(replace “install” with “lmake” and repeat the command)

- Execute the LPS_makedir script:

cd /usr/cm/LPS

LPS_makedir

- Check the structure.

- b. If the directory structure remains unchanged, copy the script to the lpswork directory so it can be checked into PVCS with the delivered software:

cp LPS_makedir /\$LPS_HOME

3.2.1.5 Verify User Environment Setup

The CM administrator must have the following statements in the CM .cshrc file to build in the development environment:

- **setenv LPS_HOME \$HOME/lpswork**
- **setenv HOME /usr/cm**
- **setenv PVCSHOME /usr/pvcs**
- **setenv PATH \$PVCSHOME/.\$PATH**
- **setenv PVCS_LPS /usr/pvcs/LPS**
- **setenv INIT_HOME \$HOME**
- **setenv CM_HOME \$HOME/LPS**
- **source .lpsdevrc** (developers build environment variables)
- **source .lpsrc** [test (system test/acceptance test) build environment variables]

Note: Only csh is supported.

Reference 4 documents the development environment variables for the LPS environment and for each subsystem's environment. Appendix D in Reference 1 describes the variables for the system test and the LPS operating environment.

3.2.1.6 Check Modified and New Units into PVCS

Assign the new version label to the current release stored in PVCS before checking delivered units into PVCS. Within the CM directory, all new and modified units are copied in the appropriate subdirectory of the work directory so they can be checked into PVCS. This includes any scripts involved, plus the LPS_makedir script, which will require at least a change in the version label for every build. Only one copy each of the lmake and install scripts is needed in PVCS and should be stored in the /usr/pvcs/LPS/archives directory. The other copies can be removed from the LPS structure. Also, .a files are not checked into PVCS.

Once all the units are checked into PVCS, they are no longer in the lpswork directory. Analyze why any remaining units did not get checked into PVCS. New units will have to be promoted to the integration test (IT) level. Identify any deleted units listed in the turnover package and remove the associated group label and the nonapplicable version label.

- To assign a new version label (i.e., R3.0) to the current release (i.e., R2.1) stored in PVCS:

```
vcs -vR3.0:R2.1 /usr/pvcs/LPS/<path>/<filename>,v
```

- To promote new units to IT:

```
vcs -gIT /usr/pvcs/LPS/<path>/<newfilename>,v
```

- To view the PVCS unit:

```
vlog /usr/pvcs/LPS/<path>/<filename>,v
```

- To remove the associated group label:

```
vcs -gAT:delete /usr/pvcs/LPS/<path>/<filename>,v
```

- To remove the nonapplicable version label:

```
vcs -vR3.0:delete /usr/pvcs/LPS/<path>/<filename>,v
```

3.2.2 Detailed Build Process Using the Command Line Version

Once all preparations are complete as described in Section 3.2.1, follow the instructions in the turnover package to perform the following build activities:

- Extract the LPS_makedir script to build the LPS structure tree.
- Extract units from PVCS into the CM work directory for the appropriate release
- Perform the build using the extracted units in the CM work directory.

- Populate the system test site.

The “new_get” script is executed to extract the appropriate units from PVCS and place them in the appropriate subdirectories in the CM work directory. When the LPS software is appropriately structured and the variables’ paths are verified, the build script is executed.

Output reports are generated during a build and are stored in /usr/cm/reports for verification.

3.2.2.1 Build the LPS Directory Structure

The following steps outline how to prepare to extract units from PVCS:

1. Login into the /usr/cm account.
2. Extract the current LPS_makedir file from PVCS if not already extracted:

```
cd /usr/cm/LPS
```

```
get vR3.0 -n $PVCS_LPS/archives/LPS_makedir,v
```
3. Check that the file is an executable and change the mode if needed:

```
ls -la (to see if file is an executable)
```

```
chmod 775 LPS_makedir (to make a file an executable)
```
4. Execute the LPS_makedir script to build the LPS work directory structure:

```
cd /usr/cm/LPS
```

```
Type LPS_makedir
```
5. When completed, verify the LPS structure against the script.

3.2.2.2 Extract Units From PVCS

1. Extract the appropriate units from PVCS using the “new_get” script.

NOTE: The new_get script used should have been edited to reflect the correct R#/B# to extract the appropriate units.

```
cd /usr/cm/scripts
```

```
Type new_get
```

If binary units are maintained outside of PVCS, copy them into the appropriate directory (refer to the turnover package).

Verify that the correct units have been extracted by comparing the directories against the directory delivered by the developers.

```
dircmp -w120 lpswork dev_deliv >& filename
```

2. Validate the HDF link between /usr/cm/LPS/hdf and /usr/cm/lpswork/COTS/hdf.

ls -la /usr/cm/lpswork/COTS

You should see this line in the list: /usr/cm/lpswork/COTS/hdf --> /usr/cm/LPS/hdf

To create the correct link:

cd \$LPS_HOME/COTS

ln -s \$CM_HOME/hdf hdf

3. Validate the other environment variables for \$HOME, \$LPS_HOME, \$INIT_HOME.

echo \$INIT_HOME (should be \$HOME)

4. Backup the lpswork directory before executing the build and reset the hdf link:

cd \$HOME

cp -R lpswork lpswork.bak

cd lpswork.bak/COTS

rm hdf

ln -s \$CM_HOME/hdf hdf

3.2.2.3 Build Executables

Compile LPS as follows:


1. Create a script file to record the build; type **script outputfile.tscr**
2. Go to scripts directory in the lpswork structure: **cd \$LPS_SCRIPTS**
3. Execute the build script: **install_lps nodebug**
4. Once the build is complete, type “exit” to discontinue recording the build
5. Check the
 - Executables in /usr/cm/lpswork/bin against the list of executables in the turnover/delivery package
 - File (filename.tscr) for error messages: **MORE filename.tscr |grep “ERROR:”** (other keywords to check are “unable,” “cannot,” “can’t”, and “don’t know”)
 - Build instructions in the turnover package for any special setups required for system test, such as data files or files required to be in the system test’s \$HOME account

3.2.2.4 Populate to System Test Site

1. Prepare the structure that will be populated to the test site by using the `setup_st_deliv` script. It creates the required directories and copies directories containing executables and files (including `Idp_mwd` and `Tk2Motif`) to a `r#_4_st` directory. Appendix C provides a hardcopy of the script. Note: The pound symbol (#) represents the new release or build number, as the case may be.
 - Edit the script. Change the release number “r#” in the line “`mkdir r#_4_st`” and add or delete any new subdirectories or special files as needed.
 - In the `$HOME` directory, execute the `setup_st_deliv` script. Figure 3–3 shows the directory structure of a populated test site environment.
2. Copy the `r#_4_st` directory to the test site (i.e., `/usr/LPS/st`) and verify the sizes of the files copied:

`cp -pr r#_4_st <st directory path>` (-p preserves the date)
3. Edit the `.cshrc` file and set the `LPS_HOME` path to the appropriate build (b) or release (r) number:

`setenv LPS_HOME /usr/LPS/st/r#`



¹r# = current release being tested

²Check the current turnover package for any changes.

Note: db_scripts may be delivered to recreate the database instance only; they are not required for operations.

10036739PC-007

Figure 3–3. Development Test Directory Structure

4. Rename r#_4_st to the appropriate build (b) or release (r) number:

```
cd /usr/LPS/st
```

```
mv r#_4_st r#
```

5. Edit the .lpsrc file:

Find and change any reference to r# to the appropriate release number (r#). Search for the line “setenv LPS_HOME” and edit the build or release number.

Change the ORACLE_HOME path in the .lpsrc file:

```
setenv ORACLE_HOME /usr/app/oracle/client/developer2000/1.3.1
```

6. Make sure that testers move the Idp_mwd and Tk2Motif files to their HOME directory.
7. Verify that the environment variables and paths are correct before testing begins. Appendix D provides a sample of the environment variables for system test. Note: The pound symbol (#) represents the new release number being tested.

```
cd r# and source .lpsrc
```

```
echo $LPS_HOME (should be usr/LPS/st/r#)
```

```
echo $LPS_RAWFILE_PATH (should be u01/st/r#/rawfile)
```

```
echo $LPS_OUTFILE_PATH(should be u02/st/r#/outfile)
```

```
echo $ORACLE_HOME (/usr/app/oracle/client/developer2000/1.3.1)
```

```
echo $LPS_TAPE_DEV (/dev/rmt/tps131d5)
```

```
echo $LPS_TAPE_LIBRARY_DEV (/dev/scsi/sc131d5l0)
```

```
echo $TWO_TASK (LPSDEV3_LPS) See Note in 3.3.1 and 3.3.2
```

8. Once all verification is complete, change file ownership:

```
cd /usr/LPS/st
```

```
chmod 775 r#
```

```
chown -R lpsst.st st
```

9. Have the system administrator change ownership of three RDCS executables and set user ID as follows:

```
chown root:sys rdc_Capture rdc_Transmit rdc_DeleteFiles
```

```
chmod u+s rdc_Capture rdc_Transmit rdc_DeleteFiles
```

System testing can begin. See Appendix E for a sample of the .cshrc file for lpsst.

In PVCS, promote the release software to system test:

```
vpromote -gIT/usr/pvcs/LPS/<path>/<filename>,v
```

Once system test (st) and management accepts the release, prepare an r#_4_at directory to populate the acceptance test (at) directory on lps005 at the EDC. Once the executables are in the appropriate directory (at/r#), perform steps 3 through 9 using “at” in the place of “st” where applicable. Then, in PVCS, promote the release software to acceptance test in PVCS:

```
vpromote -gST/usr/pvcs/LPS/<path>/<filename>,v
```

3.2.3 Building for Operations

Because all source code is kept in PVCS on the backup string (string 5), the software builds for the operational environment are performed in the CM work directory on the backup string. When the build is complete and accepted by the testers and operations management, the executables are transferred to the operational site. The operational directory structure is shown in Figure 3–4.

3.3 Populating the Runtime Directories

This section discusses the process of populating the runtime directories for the development system and the operational system once a build has been completed.

3.3.1 Development System

A runtime environment directory structure (Figure 3–5) exists on all LPS development hardware elements. This structure is identical for each element and contains identical directory structures for development, CM, and system test/acceptance test (Figure 3–3). The process for populating the runtime directories is the same for each test group as described in Section 3.2.2.4.

Note: The environment variables in the .lpsrc file on the development string at the EDC changes as follows:

```
setenv ORACLE_SID LPS
```

```
setenv TWO_TASK LPS5DEV_LPS
```

3.3.2 Operational System

The software configuration manager creates the runtime directory structures on all operational elements for the current release, but may require system administrator support if those directories cannot be created. The executables (Figure 3–4) are copied or transferred via File Transfer Protocol (FTP) to the /usr/LPS/ops directory on each operational string, where they will be available to each operational hardware element. The structure is the shown in Figure 3–6.

Note: Environment variables in the .lpsrc file on each operational string at the EDC change as follows:


setenv TWO_TASK LPSX_LPS

where X = string number.



10036739PC-005

Figure 3–4. Operations Directory Structure




- Ro = source for all LPS releases to date
 Rs = current release's source for that environment
 Rs-1 = previous release's source for that environment
 Rx = current release's executables for that environment
 Rx-1 = previous release's executables for that environment

¹See Figure 3-1

²See Figure 3-2

³See Figure 3-3

Figure 3-5. Development Runtime Directory Structure



¹Installation of the operating system, IRIX 6.2, automatically populates the miscellaneous CO1

²Current version of the executables; see Figure 3-4 for the operational string structure.

Figure 3-6. Operational Runtime Directory Structure

Once the system is accepted by acceptance test and operations, the executables are populated to the operational strings 1–4 via FTP and copied to string 5, /usr/LPS/ops.

- To populate to strings 1–4:

Prepare to send the build/release via FTP to another machine:

in lps005 (string 5),

cd /usr/LPS/at/r#

TAR: tar -cvf <r#ops.tar filename> <r#> & outfilename

Compress: Compress <tar file> (becomes .Z file)

- In another screen, login to the target operational machine:

telnet lps00#

cd /usr/LPS/ops

ftp lps005

cd /usr/LPS/at

get r#tarfile.Z

bye

- Uncompress the .Z file.
- Untar the .tar file: **tar -xvf r#.tar >\$ r#tar.log**.
- Perform steps 3 through 9 in Section 3.2.2.4 using “ops” in place of “st” where applicable. Note: All directories should be empty except the bin, man, and tables directories.
- Verify the executables and environment variables.

3.4 LPS Release Types

There are four types of LPS releases:

1. **Release** – Involves major functionality changes, a complete system rebuild, and goes through a complete testing cycle. Planned well in advance. (See Section 3.2.)
2. **Mini-Release** – Considered a maintenance release, and involves minor functionality changes. It can require either a full or partial rebuild, and goes through a complete testing cycle. Planned as a follow-on to a release.

3. **Patch** – Considered a means to provide critical functionality or correct mission-critical problems when sufficient time exists for a complete testing cycle. Involves a partial system rebuild.
4. **Engineering Mode** – Considered a means to provide mission-critical functionality when there is no time for a complete testing cycle. Only limited module, integration, and system testing is performed. Executables only are provided to expedite resolution of the problem. Source code and full testing of the functionality is provided in the next scheduled release, mini-release, or patch of the system.

3.4.1 Build Notes from a Mini_Release or Patch

CM retains a current copy of the LPS directory structure and source outside of PVCS to save time if a patch or mini release is required. It is copied to lpswork.

The delivered or changed units are checked into PVCS.

In lpswork, delete the old unit(s). Check out the changed unit(s) from PVCS into the appropriate directory(s).

Follow the build instruction that comes with the delivered units.

3.4.2 Build Notes for an Engineering Mode

No units are to be checked into PVCS when an engineering build occurs. Follow the build instructions to perform this type of build.

Appendix A. Checklist for LPS Software Installation

The system administrator should perform the backup restoration or installation up to step 4; CM performs steps 5 and 6; and system test performs steps 7 and 8.

☐ Use backup tape to restore system.

OR

☐ 1. Install IRIX 6.2 Operating System (see Appendix F).*

☐ 2. Install Network Time Protocol (see Appendix G).

☐ 3. Set up directory structure (see Figure 1–1).

☐ 4. Install COTS (see Section 2).*

☐ Install ORACLE Server and database instance (see Appendix H).

☐ Install HDF on string 5 only (follow vendor installation procedures to install the required version or use tape provided).

☐ 5. Install LPS executables.

If not backed up, you will have to extract the R2.0 units from PVCS and compile to create the executables (see Section 3).

☐ 6. Verify environment variables and paths (see Appendix I).

☐ 7. Perform regression tests.

☐ 8. Run LPS.

*Refer to vendor installation procedures.

Appendix B. Sample Configuration Management's .cshrc File

```
#####
# Sample .cshrc for LPS users/developers                                     #
#####
set prompt=lpsdev1:”%/ ->“

# Set up for remote protocol with other servers
if ($?USER == 0 || $?prompt == 0) exit

set path = ( . ~/bin /usr/bin /usr/bsd \
            /etc /usr/include /usr/include/sys \
            /usr/local /usr/local/bin /usr/sbin )

setenv LPS_HOME $HOME/lpswork
setenv CM_HOME $HOME/LPS
setenv INIT_HOME $HOME
setenv DELIV /u04/cm/Dev_Deliveries/r2pvcs/r3.0
setenv LOGS /u04/cm/LOGS
setenv DEV /u04/cm/Dev_Deliveries/

# Add LPS environment settings
if (-e $LPS_HOME ) then
    # Force a clean path (recommended)
    unsetenv PATH
    unsetenv MANPATH
    unsetenv LD_LIBRARY_PATH

    # Set the default path and sets up LPS operations/test environment
    # Developers/maintenance programmers use .lpsdevrc instead of .lpsrc
    source $LPS_HOME/.lpsdevrc
    # Added 1/30/98 to accommodate TWO_TASK for cm and st
    setenv TWO_TASK LPSDEV3_LPS
    source $LPS_HOME/.lpsrc
else
    echo “LPS_HOME is not available.”
    setenv PATH /usr/local/bin:/usr/bin:/bin:/usr/etc:/etc:/usr/bsd:/usr/sbin:/sbin:/usr/include:/
endif

#Setup for PVCS
setenv PVCSHOME /usr/pvcs
setenv PATH $PVCSHOME/.$PATH
setenv PVCS_LPS /usr/pvcs/LPS

# Add my own environment
setenv PATH .:$HOME/bin:$PATH

# File completion using the escape but ignoring certain extensions.
set filec
set ignore=.o
set noclobber
set ignoreeof

# Set the history
set history=40

# Set the prompt
set prompt=“`uname -n`:`whoami`:”%/[%!`] %”

#      settings for interactive shells
```

```

if ($shell == /bin/csh) then
##### PROMPT FOR csh
set prompt="`uname -n`.`whoami`.:%/[%!\\] %"

##### cd ALIAS FOR csh
alias cd `cd \!*;set prompt = "`whoami`@`uname -n`(`uname`):$cwd"\[!\]"=> "date`
endif

if ($shell == /bin/tcsh) then
##### PROMPT FOR tcsh
set prompt="`hostname`.:%/[%!\\] %"

##### ENABLE vi COMMAND LINE EDITING FOR tcsh
##### To use emacs command line editing substitute "emacs" for
##### "vi" on the next line
bind vi
endif

# Set the backspace key (Ctrl-v then backspace)
if ($TERM == sun-cmd || $TERM == xterm) then
  stty echo erase
endif

# Initialize all aliases
if (-e $HOME/.alias) then
  source $HOME/.alias
endif

set history=1000
set notify
set savehist=300

```

Appendix C. Configuration Management Scripts

This appendix provides copies of the following CM scripts:

1. `new_check` – checks units into PVCS
2. `new_get` – extracts units from PVCS
3. `LPS_makedir` – extracts `lmake` and `install` from `pvcs`, creates the LPS directory structure, copies the `lmake` and `install` files in directories, and sets up the `hdf` link between the `$HOME/LPS/hdf` and `$LPS_HOME/COTS`.
4. `setup_st_deliv` – creates the directory structure to be installed for system test.

C.1 `new_check`

```
*****
#put script – to put all of LPS into PVCS once the archive (header)is created.
#
#Changes:
#1/24/97 cm: – added /bin dir contained .scr files; added to this script.
#           – LDTS include and global lines fixed
#           – added MFPS/data subdir for parms.dat
#-1/29: added MFPS/scripts
#-Add PCDS dirs
#-4/23/97 – edited in additions
#-6/2/97 – added bin to store rdc_Terminate
#-7/2/97 – added for B3.2 IDPS/src2..src4, LDTS/src4, MACS/src5..src10
#-7/5/97 – Commented out RDCS/src1 LPS_makedir does not create it until
#-7/6/9 – B3.2 dirs added: RDCS/src/src1..src9, MACS/src/src11
#1/10/98 – (B5.0) Add db_scripts, MACS/src /src12, MACS/src/src13
*****

#!/bin/sh

echo “Working in the bin directory”
cd /u04/cm/lpswork/bin
put -vB5 -n -m”B5 Delivered Units” /u04/pvcs/LPS/bin/*,v

echo “Working in the COTS directory”
cd /u04/cm/lpswork/COTS
put -vB5 -n -m”B5 Delivered Units” /u04/pvcs/LPS/COTS/archives/*,v
cd /u04/cm/lpswork/COTS/frame_sync/src
put -vB5 -n -m”B5 Delivered Units” /u04/pvcs/LPS/COTS/frame_sync/src/*,v
cd /u04/cm/lpswork/COTS/frame_sync/include
put -vB5 -n -m”B5 Delivered Units” /u04/pvcs/LPS/COTS/frame_sync/include/*,v

echo “Working in the IDPS directory”
cd /u04/cm/lpswork/IDPS
put -vB5 -n -m”B5 Delivered Units” /u04/pvcs/LPS/IDPS/archives/*,v
cd /u04/cm/lpswork/IDPS/data
put -vB5 -n -m”B5 Delivered Units” /u04/pvcs/LPS/IDPS/data/*,v
cd /u04/cm/lpswork/IDPS/global/include
put -vB5 -n -m”B5 Delivered Units” /u04/pvcs/LPS/IDPS/global/include/*,v
cd /u04/cm/lpswork/IDPS/global/src
put -vB5 -n -m”B5 Delivered Units” /u04/pvcs/LPS/IDPS/global/src/*,v
cd /u04/cm/lpswork/IDPS/db/include
put -vB5 -n -m”B5 Delivered Units” /u04/pvcs/LPS/IDPS/db/include/*,v
cd /u04/cm/lpswork/IDPS/db/src
```

```

put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/IDPS/db/src/*,v
cd /u04/cm/lpswork/IDPS/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/IDPS/include/*,v
cd /u04/cm/lpswork/IDPS/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/IDPS/src/*,v
cd /u04/cm/lpswork/IDPS/src/src1
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/IDPS/src/src1/*,v
cd /u04/cm/lpswork/IDPS/src/src2
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/IDPS/src/src2/*,v
cd /u04/cm/lpswork/IDPS/src/src3
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/IDPS/src/src3/*,v
cd /u04/cm/lpswork/IDPS/src/src4
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/IDPS/src/src4/*,v
cd /u04/cm/lpswork/IDPS/scripts
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/IDPS/scripts/*,v

echo "Working in the LDTS directory"
cd /u04/cm/lpswork/LDTS
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/archives/*,v
cd /u04/cm/lpswork/LDTS/data
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/data/*,v
cd /u04/cm/lpswork/LDTS/db/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/db/src/*,v
cd /u04/cm/lpswork/LDTS/db/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/db/include/*,v
cd /u04/cm/lpswork/LDTS/global/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/global/src/*,v
cd /u04/cm/lpswork/LDTS/global/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/global/include/*,v
cd /u04/cm/lpswork/LDTS/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/include/*,v
cd /u04/cm/lpswork/LDTS/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/src/*,v
cd /u04/cm/lpswork/LDTS/src/src1
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/src/src1/*,v
cd /u04/cm/lpswork/LDTS/src/src2
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/src/src2/*,v
cd /u04/cm/lpswork/LDTS/src/src3
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/src/src3/*,v
cd /u04/cm/lpswork/LDTS/src/src4
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/src/src4/*,v
cd /u04/cm/lpswork/LDTS/scripts
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/LDTS/scripts/*,v

echo "Working in the MACS directory"
cd /u04/cm/lpswork/MACS
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/MACS/archives/*,v
cd /u04/cm/lpswork/MACS/data
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/MACS/data/*,v
cd /u04/cm/lpswork/MACS/db/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/MACS/db/include/*,v
cd /u04/cm/lpswork/MACS/db/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/MACS/db/src/*,v
cd /u04/cm/lpswork/MACS/global/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/MACS/global/include/*,v
cd /u04/cm/lpswork/MACS/global/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/MACS/global/src/*,v
cd /u04/cm/lpswork/MACS/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/MACS/include/*,v
cd /u04/cm/lpswork/MACS/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/MACS/src/*,v
cd /u04/cm/lpswork/MACS/src/src1
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src1/*,v
cd /u04/cm/lpswork/MACS/src/src2

```

```

put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src2/*,v
cd /u04/cm/lpswork/MACS/src/src3
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src3/*,v
cd /u04/cm/lpswork/MACS/src/src4
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src4/*,v
cd /u04/cm/lpswork/MACS/src/src5
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src5/*,v
cd /u04/cm/lpswork/MACS/src/src6
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src6/*,v
cd /u04/cm/lpswork/MACS/src/src7
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src7/*,v
cd /u04/cm/lpswork/MACS/src/src8
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src8/*,v
cd /u04/cm/lpswork/MACS/src/src9
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src9/*,v
cd /u04/cm/lpswork/MACS/src/src10
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src10/*,v
cd /u04/cm/lpswork/MACS/src/src11
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/src/src11/*,v
cd /u04/cm/lpswork/MACS/src/src12
put -vB5.0 -n -m "B5.0 Delivered Units" /u04/pvcs/LPS MACS
cd /u04/cm/lpswork/MACS/src/src13
put -vB5.0 -n -m "B5.0 Delivered Units" /u04/pvcs/LPS MACS

cd /u04/cm/lpswork/MACS/scripts
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MACS/scripts/*,v

echo "Working in the MFPS directory"
cd /u04/cm/lpswork/MFPS
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MFPS/archives/*,v
cd /u04/cm/lpswork/MFPS/data
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MFPS/data/*,v
cd /u04/cm/lpswork/MFPS/db/src
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MFPS/db/src/*,v
cd /u04/cm/lpswork/MFPS/global/include
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MFPS/global/include/*,v
cd /u04/cm/lpswork/MFPS/global/src
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MFPS/global/src/*,v
cd /u04/cm/lpswork/MFPS/include
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MFPS/include/*,v
cd /u04/cm/lpswork/MFPS/src
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MFPS/src/*,v
cd /u04/cm/lpswork/MFPS/scripts
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/MFPS/scripts/*,v

echo "Working in the PCDS directory"
cd /u04/cm/lpswork/PCDS
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/PCDS/archives/*,v
cd /u04/cm/lpswork/PCDS/data
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/PCDS/data/*,v
cd /u04/cm/lpswork/PCDS/db
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/PCDS/db/*,v
cd /u04/cm/lpswork/PCDS/db/include
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/PCDS/db/include/*,v
cd /u04/cm/lpswork/PCDS/db/src
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/PCDS/db/src/*,v
cd /u04/cm/lpswork/PCDS/global/include
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/PCDS/global/include/*,v
cd /u04/cm/lpswork/PCDS/global/src
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/PCDS/global/src/*,v
cd /u04/cm/lpswork/PCDS/include
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/PCDS/include/*,v
cd /u04/cm/lpswork/PCDS/scripts
put -vB5 -n -m "B5 Delivered Units" /u04/pvcs/LPS/PCDS/scripts/*,v

```

```

cd /u04/cm/lpswork/PCDS/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/PCDS/src/*,v

echo "Working in the RDCS directory"
cd /u04/cm/lpswork/RDCS
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/archives/*,v
cd /u04/cm/lpswork/RDCS/data
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/data/*,v
cd /u04/cm/lpswork/RDCS/bin
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/bin/*,v
cd /u04/cm/lpswork/RDCS/db/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/db/src/*,v
cd /u04/cm/lpswork/RDCS/global/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/global/include/*,v
cd /u04/cm/lpswork/RDCS/global/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/global/src/*,v
cd /u04/cm/lpswork/RDCS/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/include/*,v
cd /u04/cm/lpswork/RDCS/scripts
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/scripts/*,v
cd /u04/cm/lpswork/RDCS/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/src/*,v
cd /u04/cm/lpswork/RDCS/src/src1
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/src/src1/*,v
cd /u04/cm/lpswork/RDCS/src/src2
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/src/src2/*,v
cd /u04/cm/lpswork/RDCS/src/src3
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/src/src3/*,v
cd /u04/cm/lpswork/RDCS/src/src4
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/src/src4/*,v
cd /u04/cm/lpswork/RDCS/src/src5
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/src/src5/*,v
cd /u04/cm/lpswork/RDCS/src/src6
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/src/src6/*,v
cd /u04/cm/lpswork/RDCS/src/src7
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/src/src7/*,v
cd /u04/cm/lpswork/RDCS/src/src8
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/src/src8/*,v
cd /u04/cm/lpswork/RDCS/src/src9
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDCS/src/src9/*,v

echo "Working in the RDPS directory"
cd /u04/cm/lpswork/RDPS
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDPS/archives/*,v
cd /u04/cm/lpswork/RDPS/data
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDPS/data/*,v
cd /u04/cm/lpswork/RDPS/db/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDPS/db/src/*,v
cd /u04/cm/lpswork/RDPS/global/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDPS/global/include/*,v
cd /u04/cm/lpswork/RDPS/global/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDPS/global/src/*,v
cd /u04/cm/lpswork/RDPS/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDPS/include/*,v
cd /u04/cm/lpswork/RDPS/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDPS/src/*,v
cd /u04/cm/lpswork/RDPS/scripts
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/RDPS/scripts/*,v

echo "Working in the lpswork directory"
cd /u04/cm/lpswork
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/archives/*,v
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/archives/*,v

```

```

#scripts that extract from RCS (e.g. tco)
cd /u04/cm/lpswork/RCS_scripts
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/archives/*,v

echo "Working in the data directory"
cd /u04/cm/lpswork/data
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/data/*,v

echo "Working in the db_scripts directory"
cd /u04/cm/lpswork/db_scripts
put -vB5.0 -n -m "B5.0 Delivered Units" /u04/pvcs/LPS/db_scripts

echo "Working in the db directory"
cd /u04/cm/lpswork/db/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/db/include/*,v
cd /u04/cm/lpswork/db/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/db/src/*,v

echo "Working in the global directory"
cd /u04/cm/lpswork/global/include
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/global/include/*,v
cd /u04/cm/lpswork/global/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/global/src/*,v

echo "Working in the scripts directory"
cd /u04/cm/lpswork/scripts
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/scripts/*,v

echo "Working in the tables directory"
cd /u04/cm/lpswork/tables
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/tables/*,v

echo "Working in the ui directory"
cd /u04/cm/lpswork/ui/src
put -vB5 -n -m"B5 Delivered Units" /u04/pvcs/LPS/ui/src/*,v

```

C.2 new_get

```

#*****
#new_check script: to get units from PVCS for b31
# If the directory structure changes, copy the new_check to new_get
# so structure is the same else just change the v#.

#
#
#1/24/97 cm: - added /bin dir contained .scr files; added to this script.
#           - LDTS include and global lines fixed
#           - added MFPS/data subdir for parms.dat
#-1/29: added MFPS/scripts
#-Add PCDS dirs
#-4/23/97 - edited in additions
#-6/2/97 - added bin to store rdc_Terminate
#-7/2/97 - added for B3.1 IDPS/src2..src4, LDTS/src4, MACS/src5..src10
#-7/5/97 - For B3.1:Commented out RDCS/src1 LPS_mkdir does not create it until
#           B3.2 and copied b31new_check to b31new_get
#   Edited the get string a get command:
#   i.e.: get -vB3.2 -n $PVCS_LPS/MFPS/data/*,v
#           Only need .files from PVCS/LPS/archives (/*,v) ;so,
#           commented out the PVCS/LPS/archives/*,v and the
#           RCS_scripts contain the tco and misc RCS files.
# 7/14/97 - Edited in macs(src11) and RDCS(src1-src9) for b3.2
# 7/15/97 - changed B3.1 to B3.2 for test of getb3.2
# 7/17/97 - changed B3.2 to R2.0

```

```
# 7/24/97 – added .tco,v extract*,v and mkdir*,v to the get RCS scripts
#      section to prevent the lmake, install and LPS_mkdir
#      from being extracted a 2nd time. The RCS scripts
#      are no longer delivered after bld3.1.
# 1/16/98 R3.0 – added MACS/src/src12 and src13, dbscripts
#*****
```

```
#!/bin/sh
```

```
echo "Working in the bin directory"
cd /u04/cm/lpswork/bin
get -vR3.0 -n $PVCS_LPS/bin/*,v
```

```
echo "Working in the COTS directory"
cd /u04/cm/lpswork/COTS
get -vR3.0 -n $PVCS_LPS/COTS/archives/*,v
cd /u04/cm/lpswork/COTS/frame_sync/src
get -vR3.0 -n $PVCS_LPS/COTS/frame_sync/src/*,v
cd /u04/cm/lpswork/COTS/frame_sync/include
get -vR3.0 -n $PVCS_LPS/COTS/frame_sync/include/*,v
```

```
echo "Working in the IDPS directory"
cd /u04/cm/lpswork/IDPS
get -vR3.0 -n $PVCS_LPS/IDPS/archives/*,v
cd /u04/cm/lpswork/IDPS/data
get -vR3.0 -n $PVCS_LPS/IDPS/data/*,v
cd /u04/cm/lpswork/IDPS/global/include
get -vR3.0 -n $PVCS_LPS/IDPS/global/include/*,v
cd /u04/cm/lpswork/IDPS/global/src
get -vR3.0 -n $PVCS_LPS/IDPS/global/src/*,v
cd /u04/cm/lpswork/IDPS/db/include
get -vR3.0 -n $PVCS_LPS/IDPS/db/include/*,v
cd /u04/cm/lpswork/IDPS/db/src
get -vR3.0 -n $PVCS_LPS/IDPS/db/src/*,v
cd /u04/cm/lpswork/IDPS/include
get -vR3.0 -n $PVCS_LPS/IDPS/include/*,v
cd /u04/cm/lpswork/IDPS/src
get -vR3.0 -n $PVCS_LPS/IDPS/src/*,v
cd /u04/cm/lpswork/IDPS/src/src1
get -vR3.0 -n $PVCS_LPS/IDPS/src/src1/*,v
cd /u04/cm/lpswork/IDPS/src/src2
get -vR3.0 -n $PVCS_LPS/IDPS/src/src2/*,v
cd /u04/cm/lpswork/IDPS/src/src3
get -vR3.0 -n $PVCS_LPS/IDPS/src/src3/*,v
cd /u04/cm/lpswork/IDPS/src/src4
get -vR3.0 -n $PVCS_LPS/IDPS/src/src4/*,v
cd /u04/cm/lpswork/IDPS/scripts
get -vR3.0 -n $PVCS_LPS/IDPS/scripts/*,v
```

```
echo "Working in the LDTS directory"
cd /u04/cm/lpswork/LDTS
get -vR3.0 -n $PVCS_LPS/LDTS/archives/*,v
cd /u04/cm/lpswork/LDTS/data
get -vR3.0 -n $PVCS_LPS/LDTS/data/*,v
cd /u04/cm/lpswork/LDTS/db/src
get -vR3.0 -n $PVCS_LPS/LDTS/db/src/*,v
cd /u04/cm/lpswork/LDTS/db/include
get -vR3.0 -n $PVCS_LPS/LDTS/db/include/*,v
cd /u04/cm/lpswork/LDTS/global/src
get -vR3.0 -n $PVCS_LPS/LDTS/global/src/*,v
cd /u04/cm/lpswork/LDTS/global/include
get -vR3.0 -n $PVCS_LPS/LDTS/global/include/*,v
cd /u04/cm/lpswork/LDTS/include
get -vR3.0 -n $PVCS_LPS/LDTS/include/*,v
```

```

cd /u04/cm/lpswork/LDTS/src
get -vR3.0 -n $PVCS_LPS/LDTS/src/*,v
cd /u04/cm/lpswork/LDTS/src/src1
get -vR3.0 -n $PVCS_LPS/LDTS/src/src1/*,v
cd /u04/cm/lpswork/LDTS/src/src2
get -vR3.0 -n $PVCS_LPS/LDTS/src/src2/*,v
cd /u04/cm/lpswork/LDTS/src/src3
get -vR3.0 -n $PVCS_LPS/LDTS/src/src3/*,v
cd /u04/cm/lpswork/LDTS/src/src4
get -vR3.0 -n $PVCS_LPS/LDTS/src/src4/*,v
cd /u04/cm/lpswork/LDTS/scripts
get -vR3.0 -n $PVCS_LPS/LDTS/scripts/*,v

echo "Working in the MACS directory"
cd /u04/cm/lpswork/MACS
get -vR3.0 -n $PVCS_LPS/MACS/archives/*,v
cd /u04/cm/lpswork/MACS/data
get -vR3.0 -n $PVCS_LPS/MACS/data/*,v
cd /u04/cm/lpswork/MACS/db/include
get -vR3.0 -n $PVCS_LPS/MACS/db/include/*,v
cd /u04/cm/lpswork/MACS/db/src
get -vR3.0 -n $PVCS_LPS/MACS/db/src/*,v
cd /u04/cm/lpswork/MACS/global/include
get -vR3.0 -n $PVCS_LPS/MACS/global/include/*,v
cd /u04/cm/lpswork/MACS/global/src
get -vR3.0 -n $PVCS_LPS/MACS/global/src/*,v
cd /u04/cm/lpswork/MACS/include
get -vR3.0 -n $PVCS_LPS/MACS/include/*,v
cd /u04/cm/lpswork/MACS/src
get -vR3.0 -n $PVCS_LPS/MACS/src/*,v
cd /u04/cm/lpswork/MACS/src/src1
get -vR3.0 -n $PVCS_LPS/MACS/src/src1/*,v
cd /u04/cm/lpswork/MACS/src/src2
get -vR3.0 -n $PVCS_LPS/MACS/src/src2/*,v
cd /u04/cm/lpswork/MACS/src/src3
get -vR3.0 -n $PVCS_LPS/MACS/src/src3/*,v
cd /u04/cm/lpswork/MACS/src/src4
get -vR3.0 -n $PVCS_LPS/MACS/src/src4/*,v
cd /u04/cm/lpswork/MACS/src/src5
get -vR3.0 -n $PVCS_LPS/MACS/src/src5/*,v
cd /u04/cm/lpswork/MACS/src/src6
get -vR3.0 -n $PVCS_LPS/MACS/src/src6/*,v
cd /u04/cm/lpswork/MACS/src/src7
get -vR3.0 -n $PVCS_LPS/MACS/src/src7/*,v
cd /u04/cm/lpswork/MACS/src/src8
get -vR3.0 -n $PVCS_LPS/MACS/src/src8/*,v
cd /u04/cm/lpswork/MACS/src/src9
get -vR3.0 -n $PVCS_LPS/MACS/src/src9/*,v
cd /u04/cm/lpswork/MACS/src/src10
get -vR3.0 -n $PVCS_LPS/MACS/src/src10/*,v
cd /u04/cm/lpswork/MACS/src/src11
get -vR3.0 -n $PVCS_LPS/MACS/src/src11/*,v
cd /u04/cm/lpswork/MACS/src/src12
get -vR3.0 -n $PVCS_LPS/MACS/src/src12/*,v
cd /u04/cm/lpswork/MACS/src/src13
get -vR3.0 -n $PVCS_LPS/MACS/src/src13/*,v
cd /u04/cm/lpswork/MACS/scripts
get -vR3.0 -n $PVCS_LPS/MACS/scripts/*,v

echo "Working in the MFPS directory"
cd /u04/cm/lpswork/MFPS
get -vR3.0 -n $PVCS_LPS/MFPS/archives/*,v
cd /u04/cm/lpswork/MFPS/data
get -vR3.0 -n $PVCS_LPS/MFPS/data/*,v

```

```

cd /u04/cm/lpswork/MFPS/db/src
get -vR3.0 -n $PVCS_LPS/MFPS/db/src/*,v
cd /u04/cm/lpswork/MFPS/global/include
get -vR3.0 -n $PVCS_LPS/MFPS/global/include/*,v
cd /u04/cm/lpswork/MFPS/global/src
get -vR3.0 -n $PVCS_LPS/MFPS/global/src/*,v
cd /u04/cm/lpswork/MFPS/include
get -vR3.0 -n $PVCS_LPS/MFPS/include/*,v
cd /u04/cm/lpswork/MFPS/src
get -vR3.0 -n $PVCS_LPS/MFPS/src/*,v
cd /u04/cm/lpswork/MFPS/scripts
get -vR3.0 -n $PVCS_LPS/MFPS/scripts/*,v

```

```

echo "Working in the PCDS directory"
cd /u04/cm/lpswork/PCDS
get -vR3.0 -n $PVCS_LPS/PCDS/archives/*,v
cd /u04/cm/lpswork/PCDS/data
get -vR3.0 -n $PVCS_LPS/PCDS/data/*,v
cd /u04/cm/lpswork/PCDS/db
get -vR3.0 -n $PVCS_LPS/PCDS/db/*,v
cd /u04/cm/lpswork/PCDS/db/include
get -vR3.0 -n $PVCS_LPS/PCDS/db/include/*,v
cd /u04/cm/lpswork/PCDS/db/src
get -vR3.0 -n $PVCS_LPS/PCDS/db/src/*,v
cd /u04/cm/lpswork/PCDS/global/include
get -vR3.0 -n $PVCS_LPS/PCDS/global/include/*,v
cd /u04/cm/lpswork/PCDS/global/src
get -vR3.0 -n $PVCS_LPS/PCDS/global/src/*,v
cd /u04/cm/lpswork/PCDS/include
get -vR3.0 -n $PVCS_LPS/PCDS/include/*,v
cd /u04/cm/lpswork/PCDS/scripts
get -vR3.0 -n $PVCS_LPS/PCDS/scripts/*,v
cd /u04/cm/lpswork/PCDS/src
get -vR3.0 -n $PVCS_LPS/PCDS/src/*,v

```

```

Echo "Working in the RDCS directory"
cd /u04/cm/lpswork/RDCS
get -vR3.0 -n $PVCS_LPS/RDCS/archives/*,v
cd /u04/cm/lpswork/RDCS/data
get -vR3.0 -n $PVCS_LPS/RDCS/data/*,v
cd /u04/cm/lpswork/RDCS/bin
get -vR3.0 -n $PVCS_LPS/RDCS/bin/*,v
cd /u04/cm/lpswork/RDCS/db/src
get -vR3.0 -n $PVCS_LPS/RDCS/db/src/*,v
cd /u04/cm/lpswork/RDCS/global/include
get -vR3.0 -n $PVCS_LPS/RDCS/global/include/*,v
cd /u04/cm/lpswork/RDCS/global/src
get -vR3.0 -n $PVCS_LPS/RDCS/global/src/*,v
cd /u04/cm/lpswork/RDCS/include
get -vR3.0 -n $PVCS_LPS/RDCS/include/*,v
cd /u04/cm/lpswork/RDCS/scripts
get -vR3.0 -n $PVCS_LPS/RDCS/scripts/*,v
cd /u04/cm/lpswork/RDCS/src
get -vR3.0 -n $PVCS_LPS/RDCS/src/*,v
cd /u04/cm/lpswork/RDCS/src/src1
get -vR3.0 -n $PVCS_LPS/RDCS/src/src1/*,v
cd /u04/cm/lpswork/RDCS/src/src2
get -vR3.0 -n $PVCS_LPS/RDCS/src/src2/*,v
cd /u04/cm/lpswork/RDCS/src/src3
get -vR3.0 -n $PVCS_LPS/RDCS/src/src3/*,v
cd /u04/cm/lpswork/RDCS/src/src4
get -vR3.0 -n $PVCS_LPS/RDCS/src/src4/*,v
cd /u04/cm/lpswork/RDCS/src/src5
get -vR3.0 -n $PVCS_LPS/RDCS/src/src5/*,v

```

```

cd /u04/cm/lpswork/RDCS/src/src6
get -vR3.0 -n $PVCS_LPS/RDCS/src/src6/*,v
cd /u04/cm/lpswork/RDCS/src/src7
get -vR3.0 -n $PVCS_LPS/RDCS/src/src7/*,v
cd /u04/cm/lpswork/RDCS/src/src8
get -vR3.0 -n $PVCS_LPS/RDCS/src/src8/*,v
cd /u04/cm/lpswork/RDCS/src/src9
get -vR3.0 -n $PVCS_LPS/RDCS/src/src9/*,v

echo "Working in the RDPS directory"
cd /u04/cm/lpswork/RDPS
get -vR3.0 -n $PVCS_LPS/RDPS/archives/*,v
cd /u04/cm/lpswork/RDPS/data
get -vR3.0 -n $PVCS_LPS/RDPS/data/*,v
cd /u04/cm/lpswork/RDPS/db/src
get -vR3.0 -n $PVCS_LPS/RDPS/db/src/*,v
cd /u04/cm/lpswork/RDPS/global/include
get -vR3.0 -n $PVCS_LPS/RDPS/global/include/*,v
cd /u04/cm/lpswork/RDPS/global/src
get -vR3.0 -n $PVCS_LPS/RDPS/global/src/*,v
cd /u04/cm/lpswork/RDPS/include
get -vR3.0 -n $PVCS_LPS/RDPS/include/*,v
cd /u04/cm/lpswork/RDPS/src
get -vR3.0 -n $PVCS_LPS/RDPS/src/*,v
cd /u04/cm/lpswork/RDPS/scripts
get -vR3.0 -n $PVCS_LPS/RDPS/scripts/*,v

echo "Working in the lpswork directory"
cd /u04/cm/lpswork
get -vR3.0 -n $PVCS_LPS/archives/*,v
#get -vR3.0 -n $PVCS_LPS/archives/*,v

#scripts that extract from RCS (e.g. tco)
cd /u04/cm/lpswork/RCS_scripts
get -vR3.0 -n $PVCS_LPS/archives/*.tco,v
get -vR3.0 -n $PVCS_LPS/archives/makedir*,v
get -vR3.0 -n $PVCS_LPS/archives/extract*,v

echo "Working in the data directory"
cd /u04/cm/lpswork/data
get -vR3.0 -n $PVCS_LPS/data/*,v

echo "Working in the db_scripts directory"
cd /u04/cm/lpswork/db_scripts
get -vR3.0 -n $PVCS_LPS/db_scripts/*,v

echo "Working in the db directory"
cd /u04/cm/lpswork/db/include
get -vR3.0 -n $PVCS_LPS/db/include/*,v
cd /u04/cm/lpswork/db/src
get -vR3.0 -n $PVCS_LPS/db/src/*,v

echo "Working in the global directory"
cd /u04/cm/lpswork/global/include
get -vR3.0 -n $PVCS_LPS/global/include/*,v
cd /u04/cm/lpswork/global/src
get -vR3.0 -n $PVCS_LPS/global/src/*,v

echo "Working in the scripts directory"
cd /u04/cm/lpswork/scripts
get -vR3.0 -n $PVCS_LPS/scripts/*,v

echo "Working in the tables directory"
cd /u04/cm/lpswork/tables

```

```
get -vR3.0 -n $PVCS_LPS/tables/*,v
```

```
echo "Working in the ui directory"
cd /u04/cm/lpswork/ui/src
get -vR3.0 -n $PVCS_LPS/ui/src/*,v
```

C.3 LPS_makedir

```
#####
#LPS_makedir
#
#Changes:
# 4/28/97 – added RCS_scripts (where the scripts used to extract units
#   from RCS are stored until they are checked into the pvcs/LPS/archives.
# 5/12/97 – additions to the tree for b3
# 5/29/97 – added new directories for b3: IDPS/src/src1-4, LDTS/src/src4,
#   MACS/src/src5-10
# 6/20/97 – added for b3.2: MACSsrc/src11, RDCS/src/src1..src9, v#B3.2
# 7/5/97 – problem – LPS_makedir loops?? hdf had too many dir levels
# 7/13/97 – changed v# to B3.2
# 7/15/97 – changed $INIT_HOME to $CM_HOME & -vB3.2 to -gST
# 7/17/97 – changed -gST to -vR2.0 and checked into PVCS
# 1/16/98 – added dbscripts and MACS/src/src12 and src13
#####
#!/bin/sh
```

```
echo "Making directory for LPS, the directory is called lpswork"
```

```
#Must go to HOME, then get lmake from pvcs
```

```
cd $CM_HOME
```

```
get -vR3.0 /usr/pvcs/LPS/archives/lmake,v
```

```
get -vR3.0 /usr/pvcs/LPS/archives/install,v
```

```
#make the home directory
```

```
cd $HOME
```

```
mkdir lpswork
```

```
cd lpswork
```

```
    mkdir COTS
```

```
    mkdir COTS/frame_sync
```

```
    mkdir COTS/frame_sync/include
```

```
    mkdir COTS/frame_sync/src
```

```
        cp $CM_HOME/lmake COTS/frame_sync/src/.
```

```
    mkdir COTS/frame_sync/obj
```

```
    mkdir COTS/frame_sync/scripts
```

```
        cp $CM_HOME/install COTS/frame_sync/scripts/.
```

```
    ln -s $CM_HOME/hdf COTS/hdf
```

```
    mkdir DAN
```

```
    mkdir DDN
```

```
    mkdir IDPS
```

```
    mkdir IDPS/bin
```

```
    mkdir IDPS/data
```

```
    mkdir IDPS/db
```

```
    mkdir IDPS/db/include
```

```
    mkdir IDPS/db/obj
```

```
    mkdir IDPS/db/src
```

```
        cp $CM_HOME/lmake IDPS/db/src/.
```

```
    mkdir IDPS/global
```

```
    mkdir IDPS/global/include
```

```
    mkdir IDPS/global/obj
```

```
    mkdir IDPS/global/src
```

```

        cp $CM_HOME/lmake IDPS/global/src/.
mkdir IDPS/include
mkdir IDPS/obj
mkdir IDPS/scripts
cp $CM_HOME/install IDPS/scripts/.
mkdir IDPS/src
cp $CM_HOME/lmake IDPS/src/.
mkdir IDPS/src/src1
cp $CM_HOME/lmake IDPS/src/src1/.
mkdir IDPS/src/src2
cp $CM_HOME/lmake IDPS/src/src2/.
mkdir IDPS/src/src3
cp $CM_HOME/lmake IDPS/src/src3/.
mkdir IDPS/src/src4
cp $CM_HOME/lmake IDPS/src/src4/.

mkdir LDTS
mkdir LDTS/bin
mkdir LDTS/data
mkdir LDTS/db
mkdir LDTS/db/include
mkdir LDTS/db/obj
mkdir LDTS/db/src
cp $CM_HOME/lmake LDTS/db/src/.
mkdir LDTS/global
mkdir LDTS/global/include
mkdir LDTS/global/obj
mkdir LDTS/global/src
cp $CM_HOME/lmake LDTS/global/src/.
mkdir LDTS/include
mkdir LDTS/obj
mkdir LDTS/scripts
cp $CM_HOME/install LDTS/scripts/.
mkdir LDTS/src
cp $CM_HOME/lmake LDTS/src/.
mkdir LDTS/src/src1
cp $CM_HOME/lmake LDTS/src/src1/.
mkdir LDTS/src/src2
cp $CM_HOME/lmake LDTS/src/src2/.
mkdir LDTS/src/src3
cp $CM_HOME/lmake LDTS/src/src3/.
mkdir LDTS/src/src4
cp $CM_HOME/lmake LDTS/src/src4/.

mkdir MACS
mkdir MACS/bin
mkdir MACS/data
mkdir MACS/db
mkdir MACS/db/include
mkdir MACS/db/obj
mkdir MACS/db/src
cp $CM_HOME/lmake MACS/db/src/.
mkdir MACS/global
mkdir MACS/global/include
mkdir MACS/global/obj
mkdir MACS/global/src
cp $CM_HOME/lmake MACS/global/src/.
mkdir MACS/include
mkdir MACS/obj
mkdir MACS/scripts
cp $CM_HOME/install MACS/scripts/.
mkdir MACS/src
cp $CM_HOME/lmake MACS/src/.
mkdir MACS/src/src1

```

```

        cp $CM_HOME/lmake MACS/src/src1/.
mkdir MACS/src/src2
        cp $CM_HOME/lmake MACS/src/src2/.
mkdir MACS/src/src3
        cp $CM_HOME/lmake MACS/src/src3/.
mkdir MACS/src/src4
        cp $CM_HOME/lmake MACS/src/src4/.
mkdir MACS/src/src5
        cp $CM_HOME/lmake MACS/src/src5/.
mkdir MACS/src/src6
        cp $CM_HOME/lmake MACS/src/src6/.
mkdir MACS/src/src7
        cp $CM_HOME/lmake MACS/src/src7/.
mkdir MACS/src/src8
        cp $CM_HOME/lmake MACS/src/src8/.
mkdir MACS/src/src9
        cp $CM_HOME/lmake MACS/src/src9/.
mkdir MACS/src/src10
        cp $CM_HOME/lmake MACS/src/src10/.
mkdir MACS/src/src11
        cp $CM_HOME/lmake MACS/src/src11/.
mkdir MACS/src/src12
        cp $CM_HOME/lmake MACS/src/src12/.
mkdir MACS/src/src13
        cp $CM_HOME/lmake MACS/src/src13/.

mkdir MFPS
mkdir MFPS/bin
mkdir MFPS/data
mkdir MFPS/db
mkdir MFPS/db/include
mkdir MFPS/db/obj
mkdir MFPS/db/src
        cp $CM_HOME/lmake MFPS/db/src/.
mkdir MFPS/global
mkdir MFPS/global/include
mkdir MFPS/global/obj
mkdir MFPS/global/src
        cp $CM_HOME/lmake MFPS/global/src/.
mkdir MFPS/include
mkdir MFPS/obj
mkdir MFPS/scripts
        cp $CM_HOME/install MFPS/scripts/.
mkdir MFPS/src
        cp $CM_HOME/lmake MFPS/src/.

mkdir PCDS
mkdir PCDS/bin
mkdir PCDS/data
mkdir PCDS/db
mkdir PCDS/db/include
mkdir PCDS/db/obj
mkdir PCDS/db/src
        cp $CM_HOME/lmake PCDS/db/src/.
mkdir PCDS/global
mkdir PCDS/global/include
mkdir PCDS/global/obj
mkdir PCDS/global/src
        cp $CM_HOME/lmake PCDS/global/src/.
mkdir PCDS/include
mkdir PCDS/obj
mkdir PCDS/scripts
        cp $CM_HOME/install PCDS/scripts/.
mkdir PCDS/src

```

```

cp $CM_HOME/lmake PCDS/src/.

mkdir RDCS
mkdir RDCS/bin
mkdir RDCS/data
mkdir RDCS/db
mkdir RDCS/db/include
mkdir RDCS/db/obj
mkdir RDCS/db/src
    cp $CM_HOME/lmake RDCS/db/src/.
mkdir RDCS/global
mkdir RDCS/global/include
mkdir RDCS/global/obj
mkdir RDCS/global/src
    cp $CM_HOME/lmake RDCS/global/src/.
mkdir RDCS/include
mkdir RDCS/obj
mkdir RDCS/scripts
    cp $CM_HOME/install RDCS/scripts/.
mkdir RDCS/src
    cp $CM_HOME/lmake RDCS/src/.
mkdir RDCS/src/src1
    cp $CM_HOME/lmake RDCS/src/src1/.
mkdir RDCS/src/src2
    cp $CM_HOME/lmake RDCS/src/src2/.
mkdir RDCS/src/src3
    cp $CM_HOME/lmake RDCS/src/src3/.
mkdir RDCS/src/src4
    cp $CM_HOME/lmake RDCS/src/src4/.
mkdir RDCS/src/src5
    cp $CM_HOME/lmake RDCS/src/src5/.
mkdir RDCS/src/src6
    cp $CM_HOME/lmake RDCS/src/src6/.
mkdir RDCS/src/src7
    cp $CM_HOME/lmake RDCS/src/src7/.
mkdir RDCS/src/src8
    cp $CM_HOME/lmake RDCS/src/src8/.
mkdir RDCS/src/src9
    cp $CM_HOME/lmake RDCS/src/src9/.

mkdir RDPS
mkdir RDPS/bin
mkdir RDPS/data
mkdir RDPS/db
mkdir RDPS/db/include
mkdir RDPS/db/obj
mkdir RDPS/db/src
    cp $CM_HOME/lmake RDPS/db/src/.
mkdir RDPS/global
mkdir RDPS/global/include
mkdir RDPS/global/obj
mkdir RDPS/global/src
    cp $CM_HOME/lmake RDPS/global/src/.
mkdir RDPS/include
mkdir RDPS/obj
mkdir RDPS/scripts
    cp $CM_HOME/install RDPS/scripts/.
mkdir RDPS/src
    cp $CM_HOME/lmake RDPS/src/.

mkdir bin

mkdir data

```

```

mkdir db_scripts

mkdir db
mkdir db/include
mkdir db/obj
mkdir db/src
    cp $CM_HOME/lmake db/src/.

mkdir global
mkdir global/include
mkdir global/obj
mkdir global/src
    cp $CM_HOME/lmake global/src/.

mkdir journal

mkdir man

mkdir reports

mkdir RCS_scripts

mkdir scripts

mkdir tables

mkdir tools
mkdir tools/bin
mkdir tools/include
mkdir tools/obj
mkdir tools/src
    cp $CM_HOME/lmake tools/src/.

mkdir troublefile

mkdir ui
mkdir ui/bin
mkdir ui/include
mkdir ui/obj
mkdir ui/src
    cp $CM_HOME/lmake ui/src/.

#setenv CM_HOME $HOME/lpswork
echo "lpswork directory built"

```

C.4 setup_st_deliv

This script can be used to set up an “at” directory also.

```

#set_st_deliv : is to set up the structure for st that will be ftp'd to st machine
# Process:
# change the b# in the script before proceeding "mkdir b##_4_st" and "cd b##_4_st"
# 7/6/97 – added notes and cp bin to dir.
# 7/14/97 – added mkdir schedules and iasparms
# 7/31/97 – cleaned up for R2.0; changes expected for 2.1
# 1/16/98 – changed Tk2Motif line, added man directory
#*****
#*Changes
#
#
cd $HOME/Deliv_4_st/b32p1_delst
mkdir b32p1_4_st
cd b32p1_4_st

```

```
mkdir DAN
mkdir DDN
mkdir troublefile
mkdir reports
mkdir schedules
mkdir iasparms

#bin & tables dirs will be made when copying the bin and tables from lpswork
cp -pr $LPS_HOME/bin.
cp -pr $LPS_HOME/tables
cp -pr $LPS_HOME/man

cp $LPS_HOME/.lpsrc

cp $LPS_HOME/IDPS/src/src4/Idp_mwd

cp $LPS_HOME/ui/src/Tk2Motif

echo "Have System Administrator change ownership to root of"
echo "rdc_Capture, rdc_Transmit, rdc_DeleteFiles"
echo "and to set user ID: chmod u+s <each file>"
echo "If debug build is complete, copy the bin into the st deliv as d_bin"
```

Appendix D. Sample Environment Variables for System Test

*These variables are machine-dependent.

**/u03 was used due to space problems in /u02

```
HOME=/usr/lpsdev/lpsst
LOGNAME=lpsst
HZ=100
TZ=GMT0GMT
TERM=iris-ansi-net
USER=lpsst
LANG=C
SHELL=/bin/tcsh
*REMOTEHOST=l7ws007.gsfc.nasa.gov
REMOTEUSER=UNKNOWN
MAIL=/usr/mail/lpsst
*DISPLAY=l7ws007:0.0
SHLVL=1
PWD=/usr/lpsdev/lpsst
*HOST=lpsdev3
HOSTTYPE=iris4d
MSGVERB=text:action
NOMSGLABEL=1
NOMSGSEVERITY=1
LD_LIBRARYN32_PATH=/usr/lib32
LD_LIBRARY64_PATH=/usr/lib64
LPS_HOME=/usr/LPS/st/r3
PATH=./usr/LPS/st/r3/bin:/usr/lpsdev/lpsst/tools:/usr/app/oracle/client/developer2000/1.3.1/bin:/usr/LPS/st/r3/bin:/usr/app/oracle/client/developer2000/1.3.1/bin:/usr/bin/X11:/usr/local/bin:/usr/bin:/bin:/usr/etc:/etc:/usr/bsd:/usr/sbin:/sbin
MANPATH=/usr/LPS/st/r3/man:/usr/share/catman:/usr/share/man:/usr/catman:/usr/local/man
LD_LIBRARY_PATH=/usr/app/oracle/client/developer2000/1.3.1/lib:/usr/lib
X11HOME=/usr/bin/X11
XNLSPATH=/usr/motif/lib/X11/nls
ORACLE_HOME=/usr/app/oracle/client/developer2000/1.3.1
ORACLE_PATH=/usr/app/oracle/client/developer2000/1.3.1/bin:/usr/bin/X11:/usr/local/bin:/usr/bin:/bin:/usr/etc:/etc:/usr/bsd:/usr/sbin:/sbin
ORACLE_SID=LPS
ORACLE_TERM=xterm
TNS_ADMIN=/usr/app/oracle/client/developer2000/1.3.1/tns
*TWO_TASK=LPSDEV3_LPS
LPS_BIN=/usr/LPS/st/r3/bin
LPS_DANFILE_PATH=/usr/LPS/st/r3/DAN
LPS_DDNFILE_PATH=/usr/LPS/st/r3/DDN
LPS_JOURNAL_PATH=/usr/LPS
**LPS_OUTFILE_PATH=/u03/st/r3/outfile
LPS_RAWFILE_PATH=/u01/st/r3/rawfile
LPS_REPORT_PATH=/usr/LPS/st/r3/reports
LPS_TAPE_DEV=/dev/rmt/tps131d5
LPS_TABLE_PATH=/usr/LPS/st/r3/tables
LPS_TEMPFILE_PATH=/usr/LPS/st/r3/tmp
**LPS_TROUBLEFILE_PATH=/u03/st/r3/troublefile
LPS_IAS_PARMS_PATH=/usr/LPS/st/r3/iasparms
LPS_CONT_SCHED_PATH=/usr/LPS/st/r3/schedules
LPS_PRINTER_DEVICE=/dev/plp
LPS_TAPE_LIBRARY_DEV=/dev/scsi/sc131d5l0
RDC_DEVICE=/dev/hpdiB
```

```
RDC_STATUS_INTERVAL=30
RDC_THRESH_SYSTEMDISK=0.01
LPS_CAPTURE_PROCESSOR=1
FORMS45_PATH=/usr/LPS/st/r3/bin
REPORTS25_PATH=/usr/LPS/st/r3/bin
ENV=/usr/lpsdev/lpsst/.kshrc
```

Appendix E. Sample Tester's .cshrc File

```
#####  
# Sample .cshrc for LPS users/developers                                     #  
#####  
  
alias data cd /u02/data  
alias hpdi cd /usr/people/hpdi  
# Set up for remote protocol with other servers  
if ($?USER == 0 || $?prompt == 0) exit  
  
# Set up LPS_HOME (tailor it to your LPS_HOME)  
setenv LPS_HOME /usr/LPS/at/r3  
  
# Add LPS environment settings  
if (-e $LPS_HOME) then  
    # Force a clean path (recommended)  
    unsetenv PATH  
    unsetenv MANPATH  
    unsetenv LD_LIBRARY_PATH  
  
    # Set the default path and sets up LPS operations/test environment  
    # Developers/maintenance programmers use .lpsdevrc instead of .lpsrc  
    source $LPS_HOME/.lpsrc  
else  
    # set your own PATH  
    setenv PATH /usr/local/bin:/usr/bin:/bin:/usr/etc:/etc:/usr/bsd:/usr/sbin:/sbin  
    echo "LPS_HOME is not available."  
endif  
  
# Add my own environment  
setenv PATH ./usr/home/lpsst/bin:/export/home/lpsst/tools:$PATH  
  
# Modify default environment variables  
  
# File completion using the escape but ignoring certain extensions.  
set filec  
set ignore=.o  
  
# Set the history  
set history=40  
  
# Set the prompt  
# set prompt="uname -n:`whoami`:!:"  
set prompt="hostname`:%[%!%]` %"  
  
# Set the backspace key (Ctrl-v then backspace)  
if ($TERM == sun-cmd || $TERM == xterm) then  
    stty echo erase  
endif  
  
# Initialize all aliases  
if (-e $HOME/.alias) then  
    source $HOME/.alias  
endif
```

Appendix F. Installing the IRIX Operating System

Follow the vendor's installation instructions using the following checklist:

1. Repartition the system disk if it's not already partitioned.
 - a. Select System Maintenance Menu, option 5:

boot stand/fx --x
 - b. Make filesystem (mkfs <filesystem name>) for the new partitions.
 - c. Mount new filesystem.
2. Install IRIX 6.2 CDs (Parts 1 and 2 and Documenters Workbench).
3. Install ONC3/NFS 6.2.
4. Install IRIS Development Option 6.2.
5. Install IRIX Applications May 1996.
6. Install IRIS Power C 6.2.
7. Reboot and edit the following files to contain site-dependent information (i.e., ip address or nameserver):

/etc/sys_id

/etc/hosts

/etc/passwd

/etc/hosts

/etc/resolv.conf

/etc/TIMEZONE

/etc/config/netif.options

NOTE: /etc/config/netif.options should define the following interface:

if1name=et0

if1addr=\$HOSTNAME

if2name=xpi0

if2addr=gate-\$HOSTNAME

if3name=xpi1

if3addr=gate2-\$HOSTNAME

8. Reboot again and verify network connectivity via ping or telnet.
9. Mount RAIDs as follows, if not already done:

```
mkdir /u01  
mkdir /u02  
mount /dev/dsk/dks133d1s7 /u01  
mount /dev/dsk/dks134d1s7 /u02  
mount -p > /etc/fstab
```

10. Install IRIX 6.2 recommended patches:

netscape <http://www.surf.sgi.com/SurfZone/Support/patchset/index.html>

11. Install HPDI/VSIO code.

Make the following modifications after installation is complete (you must be “root” to make them):

1. Switch user to root:

su Root

2. Edit /etc/syslog.conf:

- a. Add the following line at the end of the file:

local0.debug;kern.none /tmp/LPS_Journal

- b. Comment out:

local0.alert root, operator

- c. Save the file.

- d. Issue the **killall -HUP syslogd** command.

3. Run systune interactively by typing **systune -i**:

- a. Change semmns to 2048
- b. Change semmni to 100
- c. Quit and reboot

Appendix G. Installing Network Time Protocol

To install Network Time Protocol on each string, follow these steps:

1. Download
from IRIX 6.2 Freeware CD or SGI download site
(<http://www.sgi.com/TasteOfDT/public/freeware2.0/>)
2. Follow the vendor's installation instructions as provided on the CD or at the Internet site.
3. The location, /usr/freeware, will be created during a successful installation.

Appendix H. Installing ORACLE

H.1 Installing the ORACLE Server

The ORACLE Server (V 7.3.2) was installed following builder's installation instructions. The following responses are entered at the installer prompts:

To move around the installer window, use the tab key to move from one block to another block. Use the arrow key to move from one field to another field. To make a selection, use the space bar.

1. Login to the oracle account (default shell of ORACLE is Bourne shell).
2. Verify that the oracle home directory is /usr/app/oracle by typing:

```
pwd
```

3. Create the server directory:

```
mkdir /usr/app/oracle/product; mkdir /usr/app/oracle/product/7.3.2;
```

4. Set the environment variables. Create .profile. The content of .profile should be as follows:

```
ORACLE_SID=LPS
```

```
export ORACLE_SID
```

```
ORACLE_HOME=/usr/app/oracle/product/7.3.2
```

```
export ORACLE_HOME
```

```
ORACLE_TERM=iris
```

```
export ORACLE_TERM
```

```
LD_LIBRARY_PATH=$ORACLE_HOME/lib
```

```
export LD_LIBRARY_PATH
```

```
PATH=$ORACLE_HOME/bin:$PATH
```

```
export PATH
```

```
ORACLE_PATH=$PATH
```

```
export ORACLE_PATH
```

Execute the .profile by typing:

```
. .profile
```

5. Load the CD into the CD-ROM driver.

6. Run the installer:

```
cd /CDROM/orainst
```

```
./orainst
```

Press OK at the Welcome to the New ORACLE Installer screen.

7. Enter the following information at the prompts:

Select the Installer activity:

Install, Upgrade, or De-Install Software

Select the Installer option:

Install New Product

Enter mount point for your software installation: /usr

OK

Complete \$ORACLE_HOME location: /usr/app/oracle/product/7.3.2

OK

Do you want to create DB objects also?

Yes

Confirm (or Change) Log File Location:

Installer Log: log

SQL Log: /usr/app/oracle/product/7.3.2/orainst/sql.log

Makefile Log: /usr/app/oracle/product/7.3.2/orainst/make.log

OS Log: /usr/app/oracle/product/7.3.2/orainst/os.log

OK

For the README file /CDROM/orainst/README.FIRST:

OK

Do not display this README file in the future

OK

Select one of the following:

Install from CD-ROM

Enter your ORACLE_SID: LPS

OK

Select the native language to be installed:

American/English

Do you want to relink ORACLE product executables?

Yes

Post-installation steps that need to be run by root will be written to
/usr/app/oracle/product/7.3.2/orainst/root.sh.

OK

Install online help for:

All Products Being Installed

Do you want to install UNIX-specific documentation?

No

Install product documentation from the product documentation CD-ROM for:

No Products

Select the following products from the product list:

Advanced Replication Option 7.3.2.1.0

IRIX Specific Enhancements 7.3.2.1.0

ORACLE Intelligent Agent 7.3.2.1.0

ORACLE Names 2.0.1.1.0

ORACLE Server Manager (Motif)

ORACLE7 Distributed Database option 7.3.2.1.0

ORACLE7 Server (RDBMS) 7.3.2.1.0

ORACLE7 XA Library 1.1.1.0.0

PL/SQL V2 2.3.2.0.0

Pro*C 2.2.2.0.0

SQL*Module 1.1.4.0.0

SQL*Net (V2) 2.3.2.1.0

SQL*Plus 3.3.2.0.0

TCP/IP Protocol Adapter (V2) 2.3.2.1.0

Install

Enter the official hostname (including domain) for this server:

<host name>.<domain name>

(For example, in lps002.gsfc.nasa.gov, lps002 is the hostname and gsfc.nasa.gov is the domain name.)

OK

Enter a TCP service port for the Administration Server. 8888

OK

Enter password for the Web administration. Reenter the same password at the verifying prompt.

Select group to act as database administrator of the database:

dba

Select the OSOPER group: dba

OK

Choose storage type for database:

Filesystem-Based Database

Distribute control files over three mount points?

Yes

Enter /usr/app/oracle for all three mount points.

Select the character set for creating this database.

US7ASCII

Enter passwords for SYSTEM and SYS. Reenter the same password at the verifying prompt.

Do you want to set the passwords for the internal users (dba and operator)?

No

Enter the password for the TNS listener.

Would you like MTS (Multi-Threaded Server) configured and the SQL*Net listener automatically started?

No

Do you want to use the following files as control files?

/usr/app/oracle/oradata/LPS/control01.ctl

/usr/app/oracle/oradata/LPS/control02.ctl

/usr/app/oracle/oradata/LPS/control03.ctl

Yes

The following are the default file names and sizes that will be used to create the new database. Select (OK) to continue to the next screen of defaults files.

Default file names and sizes continued. Select (Back) to see the previous screen of defaults. Select (OK) to continue.

OK

Select (Yes) to accept the default file names and sizes shown on the previous screens. Select (No) to specify new values. Select (Back) to view the previous screens.

Yes

You've selected to install the IRIX Specific Enhancements....

OK

Would you like to load the SQL*Plus Help Facility?

Yes

Would you like to load the SQL*Plus Demo Tables?

Yes

Please enter the directory where the X-Windows libraries (libXt, libX11) may be found: /usr/lib

OK

Installation of shared oracle library for Pro*C, OCI, and XA clients is complete.

OK

The requested action has been performed for selected products. Select (OK) to continue.

OK

8. Exit from the installer

At this point, directories (admin, local, oradata) are created by the installer, and the database instance creation scripts exist in the create directories.

9. Run the root.sh script as the root.

```
su root
```

```
cd $ORACLE_HOME/orainst
```

```
./root.sh
```

The following environment variables are set. Are these settings correct (Y/N)? [Y]:
Y

Enter the full pathname of the local bin directory [/opt/bin]: Return

ORACLE_HOME does not match the home directory for oracle.

Okay to continue? [N]: Y

Exit from the root account and return to the oracle account by typing: exit

10. The ORACLE instance is created and up and running. To test login, type

```
sqlplus
```

Enter user-name: system

Enter password: enter the password defined during the installation.

```
SQL> exit
```

11. Unload the CD:

```
cd      (to get the installer off the /CDROM)
```

```
eject
```

H.2 Upgrading the ORACLE Server

ORACLE server 7.3.2.2 is a patch software. It should be installed after installing 7.3.2.

1. Login to the oracle account.
2. To upgrade to a newer version, the database should be shut down:

```
svrmgrl  
SVRMGR> connect internal;  
SVRMGR> shutdown;  
SVRMGR> quit
```

3. Run the installer:

```
cd /CDROM/orainst  
./orainst
```

Press OK at the Welcome to the New ORACLE Installer screen.

4. Enter the following information at the prompts:

Select the Installer activity:

Install, Upgrade, or De-Install Software

Select the Installer option (use the Tab key to move to the selection list. Use the arrow key to go to the Add/Upgrade Software selection. Use the space bar to select the option.):

Add/Upgrade Software

OK

Enter \$ORACLE_HOME location: /usr/app/oracle/product/7.3.2

OK

Confirm (or Change) Log File Location:

Installer Log: log

SQL Log: /usr/app/oracle/product/7.3.2/orainst/sql.log

Makefile Log: /usr/app/oracle/product/7.3.2/orainst/make.log

OS Log: /usr/app/oracle/product/7.3.2/orainst/os.log

OK

For the README file /CDROM/orainst/README.FIRST :

OK

Do not display this README file in the future

OK

Select one of the following:

Install from CD-ROM

Select the native language to be installed:

American/English

OK

Relink All Executables?

Yes

The /usr/app/oracle/product/7.3.2/orainst/root.sh file already exists. Select one of the following actions:

Create new root.sh file

OK

Enter the pathname where the existing root.sh file will be saved:
/usr/app/oracle/product/7.3.2/orainst/root.sh0

OK

Post-installation steps that need to be run by root will be written to
/usr/app/oracle/product/7.3.2/orainst/root.sh.

OK

Install online help for:

All Products Being Installed

OK

Do you want to install UNIX-specific documentation?

No

Install product documentation from the product documentation CD-ROM for:

No Products

OK

Select the following products from the product list:

Advanced Replication Option 7.3.2.2.0

IRIX Specific Enhancements 7.3.2.2.0

ORACLE Context Option 1.1.2.0.0

ORACLE UNIX Installer and Documentation Viewer

ORACLE7 Distributed Database option 7.3.2.2.0

ORACLE7 Server (RDBMS) 7.3.2.2.0

ORACLE7 XA Library 7.3.2.2.0

PL/SQL V2 2.3.2.2.0

Spatial Data Option 7.3.2.2.0

Install

The currently installed version of ORACLE Common Libraries and Utilities software, 7.3.2.1.0, is out of date. The most current version is 7.3.2.2.0. Do you want to upgrade the software to 7.3.2.2.0?

Yes

The currently installed version of PL/SQL V2 software, 2.3.2.0.0, is out of date. The most current version is 2.3.2.2.0. Do you want to upgrade the software to 2.3.2.2.0?

Yes

The currently installed version of ORACLE7 Distributed Database option software, 7.3.2.1.0, is out of date. The most current version is 7.3.2.2.0. Do you want to upgrade the software to 7.3.2.2.0?

Yes

The currently installed version of Advanced Replication Option software, 7.3.2.1.0, is out of date. The most current version is 7.3.2.2.0. Do you want to upgrade the software to 7.3.2.2.0?

Yes

The currently installed version of ORACLE7 Server (RDBMS) software, 7.3.2.1.0, is out of date. The most current version is 7.3.2.2.0. Do you want to upgrade the software to 7.3.2.2.0?

Yes

Select group to act as database administrator of the database:

dba

OK

Select the OSOPER group:

dba

OK

Enter your ORACLE_SID:

LPS

OK

Does the LPS database exist and is it functional?

No

The currently installed version of IRIX Specific Enhancements software, 7.3.2.1.0, is out of date. The most current version is 7.3.2.2.0. Do you want to upgrade the software to 7.3.2.2.0?

Yes

You've selected to install the IRIX Specific Enhancements. Before using them, verify that you have the database accelerator (dba), Generic Database Accelerator Features (eoe.sw.database_accel) and patches 1167 (patchSG0001167) and 1194 (patchSG0001194) installed on your system by running the /usr/sbin/versions command.

OK

Please enter the password for the 'MDSYS' ORACLE userid:

enter the password

OK

The currently installed version of ORACLE7 XA Library software, 1.1.1.0.0, is out of date. The most current version is 7.3.2.2.0. Do you want to upgrade the software to 7.3.2.2.0?

OK

The currently installed version of SLAX: parser software, 7.3.2.1.0, is out of date. The most current version is 7.3.2.2.0. Do you want to upgrade the software to 7.3.2.2.0?

Yes

Would you like to install ORACLE Context Option demos?

Yes

Would you like to regenerate shared version of the ORACLE library for Pro*C, OCI, and XA clients?

Yes

Select (Help) for more details on what you can do next.

Select (OK) to continue.

OK

Exit from the installer.

Exit

5. Deinstall IRIX Specific Enhancements:

`cd /CDROM/orainst`

`./orainst`

Press OK at the Welcome to the New ORACLE Installer screen.

Select the Installer activity:

Install, Upgrade, or De-Install Software

OK

Select the Installer option:

De-Install Software

OK

Enter \$ORACLE_HOME location:

`/usr/app/oracle/product/7.3.2`

OK

Confirm (or Change) Log File Location:

OK

Select IRIX Specific Enhancements 7.3.2.2.0

Remove

Installer Actions Completed

Select (OK) to continue.

OK

Exit

6. Unload the CD

cd (to get the installer off the /CDROM)

eject

H.3 Creating a Database Instance

1. In the oracle account

Check if the ORACLE instance, LPS is running:

```
ps -ef | grep ora
```

(should not return ora_smon_LPS, ora_pmon_LPS, ora_dbwr_LPS, ora_lgwr_LPS, and ora_reco_LPS)

2. Modify crdbLPS.sql to change the size of the database.

```
cd /usr/app/oracle/admin/LPS/create
```

```
‘/usr/app/oracle/oradata/LPS/system01.dbf’ size 50M
```

```
‘/usr/app/oracle/oradata/LPS/redoLPS01.log’ size 2M,
```

```
‘/usr/app/oracle/oradata/LPS/redoLPS02.log’ size 2M,
```

```
‘/usr/app/oracle/oradata/LPS/redoLPS03.log’ size 2M;
```

3. Modify crdb2LPS.sql to change the size of the database.

Add spool file creation statement under the #spool 2-rdbms.lst:

```
spool /usr/app/oracle/admin/LPS/create/crdb_LPS_second.lst
```

Modify sizes:

```
create tablespace temp datafile
```

```
‘/usr/app/oracle/oradata/LPS/temp01.dbf’ size 5M
```

```
default storage (
```

```
initial 1m
```

```
next 1m
```

```
pctincrease 0
```

```
);
```

```
‘/usr/app/oracle/oradata/LPS/users01.dbf’ size 50M;
```

Create two more tablespaces. Add the following statements after creation of users tablespace:

```
REM * Create two tablespaces for application
```

```
REM *
```

```

create tablespace appl_data datafile
    '/usr/app/oracle/oradata/LPS/appl_data.dbf' size 30M
default storage(
    initial 10K
    next 10K
    pctincrease 0
    minextents 1
);
create tablespace appl_index datafile
    '/usr/app/oracle/oradata/LPS/appl_index.dbf' size 15M
default storage(
    initial 10K
    next 10K
    minextents 1
    pctincrease 0
);

```

Add the following script executing command before executing catdbsyn.sql:

```

connect internal
@/usr/app/oracle/product/7.3.2/rdbms/admin/catproc.sql

```

Add the following script executing command after executing catdbsyn.sql:

```

connect system/manager
@/usr/app/oracle/product/7.3.2/sqlplus/admin/pupbld.sql

```

4. Modify initLPS.ora and initLPS_0.ora to the following values:

```

cd /usr/app/oracle/admin/LPS/pfile
db_files = 60
#Since advanced replication option was installed
shared_pool_size = 10000000
#shared_pool_size = 3500000

```

```
# global_names = TRUE
```

Add the following parameters:

```
remote_os_authent = true
```

```
open_links = 20
```

5. Create the instance by executing the creation scripts.

```
cd /usr/app/oracle/admin/LPS/create
```

```
svrmgrl
```

```
SVRMGR> connect internal
```

```
SVRMGR> @crdbLPS.sql
```

```
SVRMGR> @crdb2LPS.sql
```

```
SVRMGR> quit
```

6. Check the instance is up and running.

```
ps -ef | grep ora
```

(should return these background processes: ora_reco_LPS, ora_pmon_LPS, ora_lgwr_LPS, ora_dbwr_LPS, and ora_smon_LPS)

7. Verify login.

```
sqlplus
```

```
Enter user-name: system
```

```
Enter password: manager (default password)
```

```
SQL> alter user system identified by xxxxx;
```

```
SQL> alter user sys identified by xxxxx;
```

```
SQL> quit
```

H.4 Creating the LPS Logical Database

1. Login to UNIX as oracle.
2. Make sure that ORACLE_HOME and ORACLE_SID are set correctly.

```
echo $ORACLE_HOME
/usr/app/oracle/product/7.3.2
echo $ORACLE_SID
LPS
```

3. If the database instance is not running, use the following procedures to start it:

```
svrmgrl
SVRMGR> connect internal
SVRMGR> startup;
SVRMGR> quit
```

At this point, no user exists.

Note: The following steps are stated in the db_creation_notes script with a minor differences.

4. Logon as system into sqlplus.

```
sqlplus system/password
```
5. Create and grant quotas for the application account owner (appldba) and grant connect role to account owner.

```
SQL> @create_appldba_user.sql
SQL> select * from all_users;
SQL> connect appldba
SQL> select * from session_privs;
SQL> connect system
```

6. Create the role(s)

```
SQL> @create_role.sql
SQL> select * from dba_roles;
```

7. Create all other users

```
SQL> @create_lpsat_user.sql          } Depends on user name
SQL> connect OPS$LPSAT/LPSAT        } Depends on user name
SQL> select * from session_privs;
SQL> connect system
```

8. Grant the role(s) to users

```
SQL> @grant_role.sql
SQL> select * from dba_role_privs;
SQL> exit;
```

9. Create the tables and sequences

```
% LPS_tables_create
Check the log file
```

10. Log into sqlplus as the account owner (appldba)

```
SQL> @create_sequence.sql
SQL> select * from seq;
```

11. Grant the table and sequence privileges to the roles.

Do EITHER A or B:

A. For role inteam_tester (CSC CM and integration testing)

```
SQL> @grant_privs_to_roles.sql
SQL> !more tmp_grants.sql
SQL> @tmp_grants.sql
SQL> connect system
SQL> set linesize 120
SQL> set pages 100
SQL> column privilege format a10
SQL> select      TABLE_NAME,PRIVILEGE,GRANTEE,OWNER      from
dba_tab_privs
> where GRANTOR='APPLDBA'
> order by TABLE_NAME,PRIVILEGE;
```

```
SQL> exit;
```

- B. For role dev_tester (EDC), exit from sqlplus, and execute this script at the UNIX prompt. The operator will be prompted for the correct Oracle account name and password.

```
% LPS_grant_privs_to_roles
```

Check the log file \$HOME/logs/cr_grant_privs.log

12. Create the public synonyms (at the UNIX prompt).

```
% LPS_synonyms_public_create
```

Check the log file \$HOME/logs/cr_synonyms.log

13. Log into sqlplus as account owner (appldba) and load the static data

```
SQL> @load_static_data.sql
```

```
SQL>select * from LPS_CONFIGURATION;
```

```
SQL>select * from LDT_dan_transfer_state;
```

```
SQL>select * from VALID_BAND_PARMS;
```

```
SQL>select * from VALID_CCSDS_PARMS;
```

```
SQL>select * from VALID_LDT_PARMS;
```

```
SQL>select * from VALID_MFP_PARMS;
```

```
SQL>select * from VALID_MFP_THRES;
```

```
SQL>select * from VALID_MWD_PARMS;
```

```
SQL>select * from VALID_PCD_PARMS;
```

```
SQL>select * from VALID_PCD_THRES;
```

```
SQL>select * from VALID_RDP_THRES;
```

14. Modify LPS_Configuration:

```
SQL>update LPS_Configuration set LPS_HARDWARE_STRING_ID = 'lps002';
```

```
SQL>update LPS_Configuration set TAPE_DEVICE_ID = '/dev/rmt/tps4d3nr';
```

Note: Both of these values are machine-dependent.

15. Load the static data for valid_wrs_parms:

Disable all constraints of the table:

```
SQL> @pre_load_wrs_parms.sql
```

```
SQL>set pagesize 100;
```

```
SQL>select * from all_constraints where table_name = 'VALID_WRS_
PARMS'
```

```
> and owner = 'APPLDBA';
```

```
SQL> exit;
```

Load the rest of the static data for valid_wrs_parms:

```
% pcd_sqlldr_command
```

Note: This will use sql loader, data file pcd_data_file.dat, and control file pcd.ctl and will write to the log file pcd.log.

Logon to sqlplus and verify data:

```
% sqlplus appldba
```

```
SQL> select count(*) from valid_wrs_parms;
```

Enable all constraints of the table

```
SQL> @post_load_wrs_parms.sql
```

```
SQL>select * from all_constraints where table_name = 'VALID_WRS_
PARMS'
```

```
> and owner = 'APPLDBA';
```

```
SQL> exit;
```

16. Load data into VALID_SENSOR_ALIGN_PARMs, UTC_UT1_CORRECTIONS, VALID_DETECTOR_GAIN_BIAS, and VALID_SCENE_PARMs from the IAS parameter file. L7CPF19970207_19970207.01 is a default IAS file name:

```
% $LPS_BIN/mac_LoadIASParms $LPS_IAS_PARMs_PATH/L7CPF19970207_
19970207.01
```

Logon to sqlplus and verify data:

```
% sqlplus appldba
```

```
SQL> select * from VALID_SENSOR_ALIGN_PARMs;
```

```
SQL> select * from UTC_UT1_CORRECTIONS;
```

```
SQL> select * from VALID_DETECTOR_GAIN_BIAS;
```

```
SQL> select * from VALID_SCENE_PARMs;
```

```
SQL> exit;
```

17. Add integrity constraints (foreign keys):

% LPS_referential

Note: The operator will be prompted for Oracle user name and password. The operator will also be prompted to either add or remove referential integrity.

Check the log file \$HOME/logs/ref_added.logdate

H.5 Updating the Logical Database

It takes anywhere from 3 to 5 hours to update the database.

H.5.1 Some Special Notes Before Starting this Procedure

1. Assumptions:
 - a. The directory \$HOME/logs has been created.
 - b. The db scripts are in directory \$HOME/b5/dbscripts.
2. Ensure that ORACLE_SID and TWO_TASK are set correctly for your machine.

ORACLE_SID = LPS

TWO_TASK = LPSDEV3_LPS (for CM)

 = LPSX_LPS (for EDC, X = string number)
3. The exp command is not recognized by all shells. We tcsh.
4. Ensure that all scripts have execute privilege.
5. The database administrator should ensure that APPLDBA has selected any table privilege, otherwise the following errors will be generated when the LPS_grant_privs_to_roles script is run. If these errors occur, they will not affect the grants; they will only affect what gets printed to the log file.

user is "APPLDBA"

FROM dba_roles

*

ERROR at line 2:

ORA-00942: table or view does not exist

FROM dba_tab_privs

*

ERROR at line 2:

ORA-00942: table or view does not exist

To grant any table privilege, do the following:

log into sqlplus as system

SQL> grant select any table to appldba;

```
SQL> exit;
```

6. Development uses the tablespace users, which was not big enough. We added a data file to tablespace users with the following command:

```
alter tablespace users
```

```
add datafile '/usr/app/oracle/oradata/LPS/users02.dbf' size 30M;
```

CM uses the tablespace appl_data, which did not have any problems with size. We are assuming that EDC is using tablespace appl_data, which should also be OK.

7. We had some problems restoring data because the rollback segments were not big enough. A script has been included in the delivery that can be run to rebuild the rollback segments on your machine, if necessary. Log into sqlplus as system to run the script:

```
SQL> @rebuild_rollback_segs.sql
```

```
SQL> exit;
```

8. The script LPS_grant_privs_to_roles assumes that the role being used is dev_tester. This script may have to be modified to specify a different role (e.g., CM may be using tester). Your database administrator should verify which role(s) is being used on your system.

H.5.2 Instructions to Alter the Database from Build 4 to Build 5 (Release 3.0)

1. Perform a full export of the database:

```
$ exp system full=y file=build5_exp_full.dmp log=build5_exp_full.log
```

2. Run script to save the data in the unaltered tables:

```
$ LPS_save_data
```

Enter the Oracle owner account name [APPLDBA]: (press <cr> or enter account name)

Export: Release 7.3.2.2.0 – Production on Thu Dec 4 15:24:46 1997

Copyright (c) Oracle Corporation 1979, 1994. All rights reserved.

Password: (enter password)

3. Run script to remove integrity constraints:

```
$ LPS_referential
```

Enter the Oracle installation account name [APPLDBA]: (press <cr> or enter account name)

Enter the Oracle installation account password: (enter password)

Enter choice to add/remove (a/r) referential integrity [r]: (enter r)

Expected error – ignore error:

```
ALTER TABLE DES_Info
```

```
*
```

ERROR at line 1:

ORA-00942: table or view does not exist

4. Run script to save the data from the tables being altered:

```
$ alter_tab_save_data
```

Enter the Oracle installation account name [APPLDBA]: (press <cr> or enter account name)

Enter the Oracle installation account password: (enter password)

5. Run script to drop and create tables owned by APPLDBA:

```
$ LPS_tables_create
```

Enter the Oracle installation account name [APPLDBA]: (press <cr> or enter account name)

Enter the Oracle installation account password: (enter password)

Expected errors - when dropping DES_Info and SD3_Tape_Info:

ERROR at line 8:

ORA-00942: table or view does not exist

ERROR at line 2:

ORA-00942: table or view does not exist

6. Run script to restore data to the altered tables:

```
$ alter_tab_restore_data
```

Enter the Oracle installation account name [APPLDBA]: press <cr> or enter account name)

Enter the Oracle installation account password: (enter password)

SPECIAL NOTE: Make sure that the data was restored correctly before dropping temp tables.

Do you want to drop temp tables (y/n)? (enter y)

7. Run script to restore data to the unaltered tables:

```
$ LPS_restore_data
```

Enter the Oracle installation account name [APPLDBA]: press <cr> or enter account name)

Password: (enter password)

Expected errors for constraints that already exist:

MP-00003: ORACLE error 2264 encountered

ORA-02264: name already used by an existing constraint

IMP-00017: following statement failed with ORACLE error 2264:

```
ALTER TABLE "VALID_PCD_THRES" ADD CONSTRAINT
```

```
"CK_VPT_NUM_MISS_DATA_WORDS"
```

```
"CHECK (Num_Missing_Data_Words >= 0)"
```

IMP-00033: Warning: Table "DES_INFO" not found in export file

IMP-00033: Warning: Table "SD3_TAPE_INFO" not found in export file

Import terminated successfully with warnings.

8. Run script to add the integrity constraints:

```
$ LPS_referential
```

Enter the Oracle installation account name [APPLDBA]: press <cr> or enter account name)

Enter the Oracle installation account password: (enter password)

Enter choice to add/remove (a/r) referential integrity [r]: (enter a)

9. Run script to create public synonyms for APPLDBA tables:

```
$ LPS_synonyms_public_create
```

Enter the Oracle system account name [SYSTEM]: (press <cr> or enter account name)

Enter the Oracle system account password: (enter password)

Enter the Oracle installation account name [APPLDBA]: (press <cr> or enter account name)

Enter the Oracle installation account password: (enter password)

An error will be generated for each synonym that already exists.

Ignore these errors.

10. Run script to grant privileges to roles:

\$ LPS_grant_privs_to_roles

Enter the Oracle installation account name [APPLDBA]: (press <cr> or enter account name)

Enter the Oracle installation account password: (enter password)

H.6 Installing the Developer 2000

1. Login to the oracle account.
2. Before running the installer, create the client and tns admin directories:
/usr/app/oracle/client/developer2000/1.3.1 and /usr/app/oracle/client/developer2000/
1.3.1/tns

```
mkdir client; cd client; mkdir developer2000; cd developer2000;  
mkdir 1.3.1; cd 1.3.1; mkdir tns;
```

3. Set the environment variables as follows:

```
ORACLE_HOME=/usr/app/oracle/client/developer2000/1.3.1  
export ORACLE_HOME  
ORACLE_SID=LPS  
export ORACLE_SID  
TNS_ADMIN=$ORACLE_HOME/tns  
export TNS_ADMIN  
ORACLE_TERM=iris  
export ORACLE_TERM  
LD_LIBRARY_PATH=$ORACLE_HOME/lib  
export LD_LIBRARY_PATH  
PATH=$ORACLE_HOME/bin:$PATH  
export PATH  
ORACLE_PATH=$PATH  
export ORACLE_PATH
```

4. Load the CD and run the installer.

```
cd /CDROM/orainst  
./orainst
```

5. Enter the following information at the prompts:

At the installer welcome window prompt, press OK.

Select the Installer activity:

Install, Upgrade, or De-Install Software

OK

Select the Installer option:

Add/Upgrade Software

OK

Enter \$ORACLE_HOME location:

/usr/app/oracle/client/developer2000/1.3.1

OK

Confirm (or Change) Log File Location:

SQL Log: /usr/app/oracle/client/developer2000/1.3.1/orainst

Makefile Log: /usr/app/oracle/client/developer2000/1.3.1/orainst

OS Log: /usr/app/oracle/client/developer2000/1.3.1/orainst

OK

For the README file /CDROM/orainst/README.FIRST :

Do not display this README file in the future

OK

Select one of the following:

Install from CD-ROM

OK

Select the native language to be installed:

American/English

OK

Do you want to relink ORACLE product executables?

Yes

Post-installation steps that need to be run by root will be written to
/usr/app/oracle/client/developer2000/1.3.1/orainst/root.sh

OK

Install online help for:

All Products Being Installed

Do you want to install UNIX-specific documentation?

No

Install product documentation from the product documentation CD-ROM for:

No Products

OK

Select the following products from the list:

ORACLE Forms 4.5.7.0.12

ORACLE Reports 2.5.5.1.1

PL/SQL Procedure Builder 1.5.6.12.1

SQL*Net (V2) 2.3.2.1.0

SQL*Plus 3.3.2.0.0

TCP/IP Protocol Adapter (V2) 2.3.2.1.0

Install

Would you like to install the PL/SQL Procedure Builder demos?

Yes

Please enter the directory where the X-Windows libraries (libXt, libX11) may be found: /usr/lib

OK

Please enter the directory where the MOTIF library (libXm) is located: /usr/lib

OK

Would you like to install the ORACLE Graphics 2.5 demos?

No

Select one or more user interfaces for ORACLE Forms...

Motif Bitmapped Interface

OK

Would you like to install the ORACLE Forms demos?

No

Select one or more user interfaces for ORACLE Reports 2.5...

Motif Bitmapped Interface

OK

Would you like to install the ORACLE Reports 2.5 demos?

No

Installation of shared oracle library for Pro*C, OCI, and XA clients is complete.

OK

The requested action has been performed for selected products. Select (OK) to continue.

OK

6. Exit from the installer

OK

7. Run the root.sh script as the root.

su root

cd \$ORACLE_HOME/orainst

./root.sh

The following environment variables are set as:

ORACLE_OWNER= oracle

ORACLE_HOME= /usr/app/oracle/client/developer2000/1.3.1

ORACLE_SID= LPS

Are these settings correct (Y/N)? [Y]:

Enter the full pathname of the local bin directory [/opt/bin]:

ORACLE_HOME does not match the home directory for oracle.

Okay to continue? [N]: Y

exit

8. Unload the CD.

cd (to get the installer off the /CDROM)

eject

9. Copy tnsnames.ora into \$TNS_ADMIN directory from LPS_TABLE_PATH/tables.

```
cp $LPS_TABLE_PATH/tables/tnsnames.ora $TNS_ADMIN
```

10. Copy listener.ora into /usr/app/oracle/product/7.3.2/network/admin cp
\$LPS_TABLE_PATH/tables/listener.ora /usr/app/oracle/product/7.3.2/network/admin

Modify listener.ora to change the host ip address to proper one.

11. Add the following into .profile

```
TNS_ADMIN=/usr/app/oracle/client/developer2000/1.3.1/tns
```

```
export
```

12. Login to the oracle account. ORACLE_HOME should point to the server directory:

```
echo $ORACLE_HOME
```

```
/usr/app/oracle/product/7.3.2
```

13. Bring up listener:

```
lsnrctl start
```

```
LSNRCTL> quit
```

14. Bring up the database instance:

```
svrmgrl
```

```
SVRMGR> connect internal;
```

```
SVRMGR> startup
```

```
SVRMGR> quit
```

15. To bring up the forms/report from any user account:

Login to an account.

Set TWO_TASK to the proper connect alias defined in tnsnames.ora

```
TWO_TASK=LPS2_LPS
```

```
export TWO_TASK
```

The following environment variables should be set.

```
ORACLE_HOME=/usr/app/oracle/client/developer2000/1.3.1
```

```
export ORACLE_HOME
```

```
TNS_ADMIN=$ORACLE_HOME/tns
```

```
export TNS_ADMIN
ORACLE_TERM=xterm
export ORACLE_TERM
LD_LIBRARY_PATH=$ORACLE_HOME/lib
export LD_LIBRARY_PATH
PATH=$ORACLE_HOME/bin:$PATH
export PATH
ORACLE_PATH=$PATH
export ORACLE_PATH
```

Run the designer to test:

```
f45desm &
```

Appendix I. Sample Environment Variables for CM

Note: The paths should be the same with the exception of the machine name, /u04. Also, the build number, where indicated (e.g., b3), will change with each build and release to reflect the current release and/or build number.

```
HOME=/u04/cm
LOGNAME=cm
HZ=100
TZ=GMT0GMT
TERM=xterms
USER=cm
LANG=C
SHELL=/bin/tcsh
REMOTEHOST=88gt250.gsfc.nasa.gov
REMOTEUSER=UNKNOWN
MAIL=/usr/mail/cm
DISPLAY=192.225.88.250:0
SHLVL=1
PWD=/u04/cm
HOST=lpsdev3
HOSTTYPE=iris4d
MSGVERB=text:action
NOMSGLABEL=1
NOMSGSEVERITY=1
LD_LIBRARYN32_PATH=/usr/lib32
LD_LIBRARY64_PATH=/usr/lib64
LPS_HOME=/u04/cm/lpswork
CM_HOME=/u04/cm/LPS
INIT_HOME=/u04/cm
DELIV=/u04/cm/Dev_Deliveries/r3b5del/b5
LOGS=/u04/cm/LOGS
DEV=/u04/cm/Dev_Deliveries
PATH=./u04/cm/bin:/usr/pvcs/./u04/cm/lpswork/ui/bin:/u04/cm/lpswork/RDPS/bin:/u04/cm/lpswork/RDCS/bin:/u04/cm/lpswork/PCDS/bin:/u04/cm/lpswork/MFPS/bin:/u04/cm/lpswork/MACS/bin:/u04/cm/lpswork/LDTS/bin:/u04/cm/lpswork/IDPS/bin:/u04/cm/lpswork/tools/bin:/u04/cm/lpswork/bin:/usr/app/oracle/product/7.3.2/bin:/usr/bin/X11:/usr/local/bin:/usr/bin:/bin:/usr/etc:/etc:/usr/bsd:/usr/sbin:/sbin:/usr/lpsdev/inteam/si/b5/COTS/hdf/hdfeos/bin/sgi
MANPATH=/u04/cm/lpswork/man:/usr/share/catman:/usr/share/man:/usr/catman:/usr/local/man
LD_LIBRARY_PATH=/usr/app/oracle/product/7.3.2/lib:/usr/lib
X11HOME=/usr/bin/X11
XNLSPATH=/usr/motif/lib/X11/nls
ORACLE_HOME=/usr/app/oracle/product/7.3.2
ORACLE_PATH=/usr/app/oracle/product/7.3.2/bin:/usr/bin/X11:/usr/local/bin:/usr/bin:/bin:/usr/etc:/etc:/usr/bsd:/usr/sbin:/sbin
ORACLE_SID=LPS
ORACLE_TERM=xterm
TNS_ADMIN=/usr/app/oracle/client/developer2000/1.3.1/tns
TWO_TASK=LPSDEV3_LPS
LPS_BIN=/u04/cm/lpswork/bin
LPS_DANFILE_PATH=/u04/cm/lpswork/DAN
LPS_DDNFILE_PATH=/u04/cm/lpswork/DDN
LPS_JOURNAL_PATH=/u04/cm/lpswork
LPS_OUTFILE_PATH=/u04/cm/lpswork/outfile
LPS_RAWFILE_PATH=/u04/cm/lpswork/rawfile
LPS_REPORT_PATH=/u04/cm/lpswork/reports
LPS_TAPE_DEV=/dev/rmt/tps131d5
LPS_TABLE_PATH=/u04/cm/lpswork/tables
LPS_TEMPFILE_PATH=/u04/cm/lpswork/tmp
LPS_TROUBLEFILE_PATH=/u04/cm/lpswork/troublefile
LPS_IAS_PARMS_PATH=/u04/cm/lpswork/iasparms
```

```

LPS_CONT_SCHED_PATH=/u04/cm/lpswork/schedules
LPS_PRINTER_DEVICE=/dev/plp
LPS_TAPE_LIBRARY_DEV=/dev/scsi/sc131d510
RDC_DEVICE=/dev/hpdiB
RDC_STATUS_INTERVAL=30
RDC_THRESH_SYSTEMDISK=0.01
LPS_CAPTURE_PROCESSOR=1
HDF_HOME=/u04/cm/lpswork/COTS/hdf/4.1r1_IRIX5.3
HDF_BIN=/u04/cm/lpswork/COTS/hdf/4.1r1_IRIX5.3/bin
HDF_INC=/u04/cm/lpswork/COTS/hdf/4.1r1_IRIX5.3/include
HDF_OBJ=/u04/cm/lpswork/COTS/hdf/4.1r1_IRIX5.3/lib
HDF_SRC=/u04/cm/lpswork/COTS/hdf/4.1r1_IRIX5.3/src
HDF_SCRIPTS=/u04/cm/lpswork/COTS/hdf/4.1r1_IRIX5.3/scripts
HDF_EOS=/u04/cm/lpswork/COTS/hdf/hdfeos
HDFEOS_HOME=/usr/lpsdev/inteam/si/b5/COTS/hdf/hdfeos
HDFLIB=/u02/lpsdev/inteam/si/b5/COTS/hdf/4.1r1_IRIX5.3/lib
HDFINC=/u02/lpsdev/inteam/si/b5/COTS/hdf/4.1r1_IRIX5.3/include
MACHINE=SGI
OSTYPE=IRIX64
BRAND=sgi
NSL_FLAG=
NSL_LIB=
CC=cc -32
F77=f77 -32
CFLAGS=-O -xansi -D_POSIX_SOURCE
C_CFH=
CFHFLAGS=-O -xansi -D_POSIX_SOURCE
C_F77_CFH=
C_F77_LIB=-li77 -liU77 -liF77
F77FLAGS=
F77_CFH=
F77_C_CFH=
CFH_F77=
F77_C_LIB=
HDFSYS=IRIS4
HDFEOS_INC=/usr/lpsdev/inteam/si/b5/COTS/hdf/hdfeos/include
HDFEOS_BIN=/usr/lpsdev/inteam/si/b5/COTS/hdf/hdfeos/bin/sgi
HDFEOS_LIB=/usr/lpsdev/inteam/si/b5/COTS/hdf/hdfeos/lib/sgi
HDFEOS_OBJ=/usr/lpsdev/inteam/si/b5/COTS/hdf/hdfeos/obj/sgi
HDFEOS_SRC=/usr/lpsdev/inteam/si/b5/COTS/hdf/hdfeos/src
COTS_HOME=/u04/cm/lpswork/COTS
DB_HOME=/u04/cm/lpswork/db
DB_INC=/u04/cm/lpswork/db/include
DB_OBJ=/u04/cm/lpswork/db/obj
DB_SRC=/u04/cm/lpswork/db/src
FS_HOME=/u04/cm/lpswork/COTS/frame_sync
FS_INC=/u04/cm/lpswork/COTS/frame_sync/include
FS_OBJ=/u04/cm/lpswork/COTS/frame_sync/obj
FS_SCRIPTS=/u04/cm/lpswork/COTS/frame_sync/scripts
FS_SRC=/u04/cm/lpswork/COTS/frame_sync/src
GLOBAL_HOME=/u04/cm/lpswork/global
GLOBAL_INC=/u04/cm/lpswork/global/include
GLOBAL_OBJ=/u04/cm/lpswork/global/obj
GLOBAL_SRC=/u04/cm/lpswork/global/src
LPS_DATA=/u04/cm/lpswork/data
LPS_SCRIPTS=/u04/cm/lpswork/scripts
TOOLS_HOME=/u04/cm/lpswork/tools
TOOLS_BIN=/u04/cm/lpswork/tools/bin
TOOLS_INC=/u04/cm/lpswork/tools/include
TOOLS_OBJ=/u04/cm/lpswork/tools/obj
TOOLS_SRC=/u04/cm/lpswork/tools/src
UI_HOME=/u04/cm/lpswork/ui
UI_BIN=/u04/cm/lpswork/ui/bin
UI_INC=/u04/cm/lpswork/ui/include

```

UI_OBJ=/u04/cm/lpswork/ui/obj
 UI_SRC=/u04/cm/lpswork/ui/src
 IDPS_HOME=/u04/cm/lpswork/IDPS
 IDPS_BIN=/u04/cm/lpswork/IDPS/bin
 IDPS_DATA=/u04/cm/lpswork/IDPS/data
 IDPS_DB=/u04/cm/lpswork/IDPS/db
 IDPS_DB_INC=/u04/cm/lpswork/IDPS/db/include
 IDPS_DB_OBJ=/u04/cm/lpswork/IDPS/db/obj
 IDPS_DB_SRC=/u04/cm/lpswork/IDPS/db/src
 IDPS_GLOBAL=/u04/cm/lpswork/IDPS/global
 IDPS_GLOBAL_INC=/u04/cm/lpswork/IDPS/global/include
 IDPS_GLOBAL_OBJ=/u04/cm/lpswork/IDPS/global/obj
 IDPS_GLOBAL_SRC=/u04/cm/lpswork/IDPS/global/src
 IDPS_INC=/u04/cm/lpswork/IDPS/include
 IDPS_OBJ=/u04/cm/lpswork/IDPS/obj
 IDPS_SCRIPTS=/u04/cm/lpswork/IDPS/scripts
 IDPS_SRC=/u04/cm/lpswork/IDPS/src
 LDTS_HOME=/u04/cm/lpswork/LDTS
 LDTS_BIN=/u04/cm/lpswork/LDTS/bin
 LDTS_DATA=/u04/cm/lpswork/LDTS/data
 LDTS_DB=/u04/cm/lpswork/LDTS/db
 LDTS_DB_INC=/u04/cm/lpswork/LDTS/db/include
 LDTS_DB_OBJ=/u04/cm/lpswork/LDTS/db/obj
 LDTS_DB_SRC=/u04/cm/lpswork/LDTS/db/src
 LDTS_GLOBAL=/u04/cm/lpswork/LDTS/global
 LDTS_GLOBAL_INC=/u04/cm/lpswork/LDTS/global/include
 LDTS_GLOBAL_OBJ=/u04/cm/lpswork/LDTS/global/obj
 LDTS_GLOBAL_SRC=/u04/cm/lpswork/LDTS/global/src
 LDTS_INC=/u04/cm/lpswork/LDTS/include
 LDTS_OBJ=/u04/cm/lpswork/LDTS/obj
 LDTS_SCRIPTS=/u04/cm/lpswork/LDTS/scripts
 LDTS_SRC=/u04/cm/lpswork/LDTS/src
 MACS_HOME=/u04/cm/lpswork/MACS
 MACS_BIN=/u04/cm/lpswork/MACS/bin
 MACS_DATA=/u04/cm/lpswork/MACS/data
 MACS_DB=/u04/cm/lpswork/MACS/db
 MACS_DB_INC=/u04/cm/lpswork/MACS/db/include
 MACS_DB_OBJ=/u04/cm/lpswork/MACS/db/obj
 MACS_DB_SRC=/u04/cm/lpswork/MACS/db/src
 MACS_GLOBAL=/u04/cm/lpswork/MACS/global
 MACS_GLOBAL_INC=/u04/cm/lpswork/MACS/global/include
 MACS_GLOBAL_OBJ=/u04/cm/lpswork/MACS/global/obj
 MACS_GLOBAL_SRC=/u04/cm/lpswork/MACS/global/src
 MACS_INC=/u04/cm/lpswork/MACS/include
 MACS_OBJ=/u04/cm/lpswork/MACS/obj
 MACS_SCRIPTS=/u04/cm/lpswork/MACS/scripts
 MACS_SRC=/u04/cm/lpswork/MACS/src
 MFPS_HOME=/u04/cm/lpswork/MFPS
 MFPS_BIN=/u04/cm/lpswork/MFPS/bin
 MFPS_DATA=/u04/cm/lpswork/MFPS/data
 MFPS_DB=/u04/cm/lpswork/MFPS/db
 MFPS_DB_INC=/u04/cm/lpswork/MFPS/db/include
 MFPS_DB_OBJ=/u04/cm/lpswork/MFPS/db/obj
 MFPS_DB_SRC=/u04/cm/lpswork/MFPS/db/src
 MFPS_GLOBAL=/u04/cm/lpswork/MFPS/global
 MFPS_GLOBAL_INC=/u04/cm/lpswork/MFPS/global/include
 MFPS_GLOBAL_OBJ=/u04/cm/lpswork/MFPS/global/obj
 MFPS_GLOBAL_SRC=/u04/cm/lpswork/MFPS/global/src
 MFPS_INC=/u04/cm/lpswork/MFPS/include
 MFPS_OBJ=/u04/cm/lpswork/MFPS/obj
 MFPS_SCRIPTS=/u04/cm/lpswork/MFPS/scripts
 MFPS_SRC=/u04/cm/lpswork/MFPS/src
 PCDS_HOME=/u04/cm/lpswork/PCDS
 PCDS_BIN=/u04/cm/lpswork/PCDS/bin

```

PCDS_DATA=/u04/cm/lpswork/PCDS/data
PCDS_DB=/u04/cm/lpswork/PCDS/db
PCDS_DB_INC=/u04/cm/lpswork/PCDS/db/include
PCDS_DB_OBJ=/u04/cm/lpswork/PCDS/db/obj
PCDS_DB_SRC=/u04/cm/lpswork/PCDS/db/src
PCDS_GLOBAL=/u04/cm/lpswork/PCDS/global
PCDS_GLOBAL_INC=/u04/cm/lpswork/PCDS/global/include
PCDS_GLOBAL_OBJ=/u04/cm/lpswork/PCDS/global/obj
PCDS_GLOBAL_SRC=/u04/cm/lpswork/PCDS/global/src
PCDS_INC=/u04/cm/lpswork/PCDS/include
PCDS_OBJ=/u04/cm/lpswork/PCDS/obj
PCDS_SCRIPTS=/u04/cm/lpswork/PCDS/scripts
PCDS_SRC=/u04/cm/lpswork/PCDS/src
RDCS_HOME=/u04/cm/lpswork/RDCS
RDCS_BIN=/u04/cm/lpswork/RDCS/bin
RDCS_DATA=/u04/cm/lpswork/RDCS/data
RDCS_DB=/u04/cm/lpswork/RDCS/db
RDCS_DB_INC=/u04/cm/lpswork/RDCS/db/include
RDCS_DB_OBJ=/u04/cm/lpswork/RDCS/db/obj
RDCS_DB_SRC=/u04/cm/lpswork/RDCS/db/src
RDCS_GLOBAL=/u04/cm/lpswork/RDCS/global
RDCS_GLOBAL_INC=/u04/cm/lpswork/RDCS/global/include
RDCS_GLOBAL_OBJ=/u04/cm/lpswork/RDCS/global/obj
RDCS_GLOBAL_SRC=/u04/cm/lpswork/RDCS/global/src
RDCS_INC=/u04/cm/lpswork/RDCS/include
RDCS_OBJ=/u04/cm/lpswork/RDCS/obj
RDCS_SCRIPTS=/u04/cm/lpswork/RDCS/scripts
RDCS_SRC=/u04/cm/lpswork/RDCS/src
RDPS_HOME=/u04/cm/lpswork/RDPS
RDPS_BIN=/u04/cm/lpswork/RDPS/bin
RDPS_DATA=/u04/cm/lpswork/RDPS/data
RDPS_DB=/u04/cm/lpswork/RDPS/db
RDPS_DB_INC=/u04/cm/lpswork/RDPS/db/include
RDPS_DB_OBJ=/u04/cm/lpswork/RDPS/db/obj
RDPS_DB_SRC=/u04/cm/lpswork/RDPS/db/src
RDPS_GLOBAL=/u04/cm/lpswork/RDPS/global
RDPS_GLOBAL_INC=/u04/cm/lpswork/RDPS/global/include
RDPS_GLOBAL_OBJ=/u04/cm/lpswork/RDPS/global/obj
RDPS_GLOBAL_SRC=/u04/cm/lpswork/RDPS/global/src
RDPS_INC=/u04/cm/lpswork/RDPS/include
RDPS_OBJ=/u04/cm/lpswork/RDPS/obj
RDPS_SCRIPTS=/u04/cm/lpswork/RDPS/scripts
RDPS_SRC=/u04/cm/lpswork/RDPS/src
CVINSTRLIB=/u04/cm
NOROLLBACK=
PVCSHOME=/usr/pvcs
PVCS_LPS=/usr/pvcs/LPS
ENV=/u04/cm/.kshrc

```

References

1. Computer Sciences Corporation, 514-3SUG/0195, *Landsat 7 Processing System (LPS) Users Guide*, Release 2, July 1997
2. —, 514-4BIP/0195, *Landsat 7 Processing System (LPS) Build Implementation Plan*, Revision 2, September 1996
3. —, 560-8SDS/0194, *Landsat 7 Processing System (LPS) Detailed Design Specification*, May 26, 1995
4. —, 514-30mm/0196, *Landsat 7 Processing System (LPS) Operations and Maintenance Manual*, Signature Copy, November 27, 1996

Acronyms

| | |
|------|--|
| CM | configuration management |
| COTS | commercial off-the-shelf |
| CSC | Computer Sciences Corporation |
| EDC | EROS Data Center |
| EOS | Earth Observing System |
| EROS | Earth Resources Observation System |
| FTP | File Transfer Protocol |
| GOTS | Government off-the-shelf |
| HDF | hierarchical data format |
| IAS | Image Assessment System |
| IDPS | image data processing subsystem |
| IT | integration test |
| LDS | LPS data transfer subsystem |
| LGS | Landsat Ground Station |
| LPS | Landsat 7 Processing System |
| MFPS | major frame processing subsystem |
| PCDS | payload correction data subsystem |
| PVCS | Polytron Version Control System |
| RAID | redundant array of inexpensive devices |
| RDCS | raw data capture subsystem |
| TAR | tape archival retrieval |